

		1'-8½" (521)	2'-0" (622)	2'-4½" (724)	2'-6" (775)	2'-8" (826)	3'-0" (927)	3'-2½" (978)	3'-4½" (1029)	3'-8" (1130)	4'-0" (1232)	
		1'-8" (508)	2'-0" (610)	2'-4" (711)	2'-6" (762)	2'-8" (813)	3'-0" (914)	3'-2" (965)	3'-4" (1016)	3'-8" (1118)	4'-0" (1219)	
		Double-Hung (DHG)										
Rough Opening	3'-0" (927)	DHG1830	DHG2030	DHG2430	DHG2630	DHG2830	DHG3030	DHG3230	DHG3430	DHG3830		
	3'-4½" (1029)	DHG1834	DHG2034	DHG2434	DHG2634	DHG2834	DHG3034	DHG3234	DHG3434	DHG3834		
	4'-0" (1232)	DHG1840	DHG2040	DHG2440	DHG2640	DHG2840	DHG3040	DHG3240	DHG3440	DHG3840	DHG4040	
	4'-6" (1384)	DHG1846	DHG2046	DHG2446	DHG2646	DHG2846	DHG3046	DHG3246	DHG3446	DHG3846	DHG4046	
	4'-9" (1461)	DHG1849	DHG2049	DHG2449	DHG2649	DHG2849	DHG3049	DHG3249	DHG3449	DHG3849	DHG4049	
	5'-0" (1537)	DHG1850	DHG2050	DHG2450	DHG2650	DHG2850	DHG3050	DHG3250	DHG3450	DHG3850	DHG4050	
	5'-1½" (1562)	DHG1851	DHG2051	DHG2451	DHG2651	DHG2851	DHG3051	DHG3251♦	DHG3451♦	DHG3851♦	DHG4051♦	
	5'-6" (1689)	DHG1856	DHG2056	DHG2456	DHG2656	DHG2856	DHG3056♦	DHG3256♦	DHG3456♦	DHG3856♦	DHG4056♦	
	6'-0" (1842)	DHG1860	DHG2060	DHG2460	DHG2660	DHG2860♦	DHG3060♦	DHG3260♦	DHG3460♦	DHG3860♦	DHG4060♦	
	6'-6" (1994)	DHG1866	DHG2066	DHG2466	DHG2666♦	DHG2866♦	DHG3066♦	DHG3266♦	DHG3466♦	DHG3866♦		
	Unit Dimension	3'-0" (914)										
		3'-4" (1016)										
		4'-0" (1219)										
		4'-6" (1372)										
		4'-9" (1448)										
		5'-0" (1524)										
	5'-1½" (1549)											
	5'-6" (1676)											
	6'-0" (1829)											
	6'-6" (1981)											

Notes:


"Unit Dimension" always refers to outside frame to frame dimension.
 "Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.
 Dimensions in parentheses are in millimeters.
 ♦ Meet or exceed clear opening area of 5.7 sq. ft. or 0.53 m², clear opening width of 20" (508) & clear opening height of 24" (610).
 Units may be ordered with sash lifts, if desired. Units 3'-0" and wider will use two sash lifts.

Taller sizes continue on page 02

Date: 1/17/17
 Scale: 1/8" (3) = 1' (305)

E-Series


Double-Hung Windows



Notes:

- "Unit Dimension" always refers to outside frame to frame dimension.
- "Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.
- Dimensions in parentheses are in millimeters.
- ◆ Meet or exceed clear opening area of 5.7 sq. ft. or 0.53 m², clear opening width of 20" (508) & clear opening height of 24" (610).
- Units may be ordered with sash lifts, if desired. Units 3'-0" and wider will use two sash lifts.

Date: 1/17/17
Scale: 1/8" (3) = 1' (305)



Taller sizes continue on page 04

Notes:

"Unit Dimension" always refers to outside frame to frame dimension.
 "Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.
 Dimensions in parentheses are in millimeters.
 ♦ Meet or exceed clear opening area of 5.7 sq. ft. or 0.53 m², clear opening width of 20" (508) & clear opening height of 24" (610).
 Units may be ordered with sash lifts, if desired. Units 3'-0" and wider will use two sash lifts. Bottom sash operates up and down, but does not tilt. Top sash is fixed.
 Units equal to or greater than 8'-0" tall are limited to 24" of clear opening height.
 Standard Units are equal light sash. However, Cottage and Reverse Cottage are available as an option with some limitations.
 Andersen Windows, Inc. reserves the right to change drawing specifications without notice

Date: 1/17/17
 Scale: 1/8" (3) = 1' (305)

Rough Opening	1'-8½"	2'-0½"	2'-4½"	2'-6½"	2'-8½"	3'-0½"	3'-2½"	3'-4½"	3'-8½"	4'-0½"	4'-6½"	5'-0½"
	(521)	(622)	(724)	(775)	(826)	(927)	(978)	(1029)	(1130)	(1232)	(1384)	(1537)
Unit Dimension	1'-8"	2'-0"	2'-4"	2'-6"	2'-8"	3'-0"	3'-2"	3'-4"	3'-8"	4'-0"	4'-6"	5'-0"
	(508)	(610)	(711)	(762)	(813)	(914)	(965)	(1016)	(1118)	(1219)	(1372)	(1524)

Monumental Single-Hung (MSH)												
Continuation from page 03												
9'-0½" (2756)												
	MSH1890	MSH2090	MSH2490	MSH2690	MSH2890	MSH3090♦	MSH3290♦	MSH3490♦	MSH3890♦	MSH4090♦	MSH4690♦	MSH5090♦
9'-6½" (2908)												
	MSH1896	MSH2096	MSH2496	MSH2696	MSH2896	MSH3096♦	MSH3296♦	MSH3496♦	MSH3896♦	MSH4096♦	MSH4696♦	
10'-0½" (3061)												
	MSH18100	MSH20100	MSH24100	MSH26100	MSH28100	MSH30100♦	MSH32100♦	MSH34100♦	MSH38100♦	MSH40100♦		

Notes:

"Unit Dimension" always refers to outside frame to frame dimension.
 "Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.
 Dimensions in parentheses are in millimeters.
 ♦ Meet or exceed clear opening area of 5.7 sq. ft. or 0.53 m², clear opening width of 20" (508) & clear opening height of 24" (610).
 Units may be ordered with sash lifts, if desired. Units 3'-0" and wider will use two sash lifts. Bottom sash operates up and down, but does not tilt. Top sash is fixed.
 Units equal to or greater than 8'-0" tall are limited to 24" of clear opening height.
 Standard Units are equal light sash. However, Cottage and Reverse Cottage are available as an option with some limitations.
 Andersen Windows, Inc. reserves the right to change drawing specifications without notice

Date: 1/17/17
 Scale: 1/8" (3) = 1' (305)


Rough Opening	Unit Dimension										
	1'-8½"	2'-0½"	2'-4½"	2'-6½"	2'-8½"	3'-0½"	3'-2½"	3'-4½"	3'-8½"	4'-0½"	5'-0½"
(521)	(622)	(724)	(775)	(826)	(927)	(978)	(1029)	(1130)	(1232)	(1537)	
(508)	(610)	(711)	(762)	(813)	(914)	(965)	(1016)	(1118)	(1219)	(1524)	

Double-Hung Transom (DHT)											
DHT1812	DHT2012	DHT2412	DHT2612	DHT2812	DHT3012	DHT3212	DHT3412	DHT3812	DHT4012	DHT5012	
DHT1814	DHT2014	DHT2414	DHT2614	DHT2814	DHT3014	DHT3214	DHT3414	DHT3814	DHT4014	DHT5014	
DHT1816	DHT2016	DHT2416	DHT2616	DHT2816	DHT3016	DHT3216	DHT3416	DHT3816	DHT4016	DHT5016	
DHT1818	DHT2018	DHT2418	DHT2618	DHT2818	DHT3018	DHT3218	DHT3418	DHT3818	DHT4018	DHT5018	
DHT1820	DHT2020	DHT2420	DHT2620	DHT2820	DHT3020	DHT3220	DHT3420	DHT3820	DHT4020	DHT5020	

Notes:

"Unit Dimension" always refers to outside frame to frame dimension.
 "Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.
 Dimensions in parentheses are in millimeters.

Date: 1/17/17
 Scale: 1/8" (3) = 1' (305)



Notes:

"Unit Dimension" always refers to outside frame to frame dimension.

"Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.

Dimensions in parentheses are in millimeters.

Date: 1/17/17

Scale: 1/8" (3) = 1' (305)