







# Big Doors

Weiland™ Pocket Liftslide  
Aluminum Wood - With Multiple Screens









## Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications.  
Dimensions in parentheses are in millimeters.

Date: 7/11/18  
Scale: None

# Big Doors

Weiland™ Pocket Liftslide  
Aluminum Wood - With Multiple Screens



## Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications.  
Dimensions in parentheses are in millimeters.

Date: 7/11/18  
Scale: None

Chart 3.0			One-Directional - One Panel									
Lock Jamb Depth = 6 ¼", Pocket Depth = 8"												
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width							
			R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.		
			Rated				Not Rated					
			Without Intermediate Stile						With Intermediate Stile			
Contact local Andersen supplier												
< 6'-6"	6'-10 ¾"	6'-8 ⅞"	2'-5 ⅝"	2'-7 ⅛"	7'-3 ⅝"	7'-5 ⅛"	12'-3 ⅝"	12'-5 ⅛"	Contact local Andersen supplier	Contact local Andersen supplier		
7'-0"	7'-4 ¾"	7'-2 ⅞"	2'-7 ⅝"	2'-9 ⅛"			7'-3 ⅝"	7'-5 ⅛"				
7'-6"	7'-10 ¾"	7'-8 ⅞"	2'-9 ⅝"	2'-11 ⅛"								
8'-0"	8'-4 ¾"	8'-2 ⅞"	2'-11 ⅝"	3'-1 ⅞"								
8'-6"	8'-10 ¾"	8'-8 ⅞"	3'-1 ⅝"	3'-3 ⅛"								
9'-0"	9'-4 ¾"	9'-2 ⅞"	3'-3 ⅝"	3'-5 ⅛"							6'-9 ⅝"	6'-11 ⅛"
9'-6"	9'-10 ¾"	9'-8 ⅞"	3'-5 ⅝"	3'-7 ⅛"							6'-5 ⅝"	6'-7 ⅝"
10'-0"	10'-4 ¾"	10'-2 ⅞"	3'-7 ⅝"	3'-9 ⅛"							6'-3 ⅝"	6'-5 ⅝"
10'-6"	10'-10 ¾"	10'-8 ⅞"	3'-9 ⅝"	3'-11 ⅛"							5'-11 ⅝"	6'-1 ⅝"
11'-0"	11'-4 ¾"	11'-2 ⅞"	3'-11 ⅝"	4'-1 ⅞"							5'-8 ⅝"	5'-10 ⅞"
11'-6"	11'-10 ¾"	11'-8 ⅞"	4'-1 ⅝"	4'-3 ⅛"	5'-5 ⅝"	5'-7 ⅝"						
12'-0"	12'-4 ¾"	12'-2 ⅞"	4'-3 ⅝"	4'-5 ⅛"	5'-3 ⅝"	5'-5 ⅝"						
> 12'-0"	Contact local Andersen supplier											






Chart 3.1			One-Directional - Two Panel								
Lock Jamb Depth = 8 1/16", O.A. Frame Depth = 11 3/4", Pocket Depth = 1'-1 9/16"											
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width						
			R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	
			Rated				Not Rated				
			Without Intermediate Stile						With Intermediate Stile		
< 6'-6"			Contact local Andersen supplier								
6'-6"	6'-10 3/4"	6'-8 7/16"	4'-4 1/8"	2'-7 1/8"	14'-0 1/8"	7'-5 1/8"	24'-0 1/8"	12'-5 1/8"	Contact local Andersen supplier	Contact local Andersen supplier	
7'-0"	7'-4 3/4"	7'-2 7/16"	4'-8 1/8"	2'-9 1/8"			14'-0 1/8"	7'-5 1/8"			
7'-6"	7'-10 3/4"	7'-8 7/16"	5'-0 1/8"	2'-11 1/8"							
8'-0"	8'-4 3/4"	8'-2 7/16"	5'-4 1/8"	3'-1 1/8"							
8'-6"	8'-10 3/4"	8'-8 7/16"	5'-8 1/8"	3'-3 1/8"							
9'-0"	9'-4 3/4"	9'-2 7/16"	6'-0 1/8"	3'-5 1/8"	13'-0 1/8"	6'-11 1/8"	14'-0 1/8"	7'-5 1/8"			
9'-6"	9'-10 3/4"	9'-8 7/16"	6'-4 1/8"	3'-7 1/8"	12'-4 1/8"	6'-7 1/8"					
10'-0"	10'-4 3/4"	10'-2 7/16"	6'-8 1/8"	3'-9 1/8"	12'-0 1/8"	6'-5 1/8"					
10'-6"	10'-10 3/4"	10'-8 7/16"	7'-0 1/8"	3'-11 1/8"	11'-4 1/8"	6'-1 1/8"					
11'-0"	11'-4 3/4"	11'-2 7/16"	7'-4 1/8"	4'-1 1/8"	10'-10 1/8"	5'-10 1/8"					
11'-6"	11'-10 3/4"	11'-8 7/16"	7'-8 1/8"	4'-3 1/8"	10'-4 1/8"	5'-7 1/8"	14'-0 1/8"	7'-5 1/8"			
12'-0"	12'-4 3/4"	12'-2 7/16"	8'-0 1/8"	4'-5 1/8"	10'-0 1/8"	5'-5 1/8"					
> 12'-0"			Contact local Andersen supplier								

Chart 3.2		One-Directional - Three Panel										
Lock Jamb Depth = 9 7⁄8", O.A. Frame Depth = 1'-5 5⁄16", Pocket Depth = 1'-7 1⁄16"												
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width							
			R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.		
			Rated				Not Rated					
			Without Intermediate Stile						With Intermediate Stile			
< 6'-6"		Contact local Andersen supplier										
6'-6"	6'-10 3⁄4"	6'-8 7⁄16"	6'-2 5⁄8"	2'-7 1⁄8"	20'-8 5⁄8"	7'-5 1⁄8"	35'-8 5⁄8"	12'-5 1⁄8"	Contact local Andersen supplier	Contact local Andersen supplier		
7'-0"	7'-4 3⁄4"	7'-2 7⁄16"	6'-8 5⁄8"	2'-9 1⁄8"			20'-8 5⁄8"	7'-5 1⁄8"				
7'-6"	7'-10 3⁄4"	7'-8 7⁄16"	7'-2 5⁄8"	2'-11 1⁄8"								
8'-0"	8'-4 3⁄4"	8'-2 7⁄16"	7'-8 5⁄8"	3'-1 1⁄8"								
8'-6"	8'-10 3⁄4"	8'-8 7⁄16"	8'-2 5⁄8"	3'-3 1⁄8"								
9'-0"	9'-4 3⁄4"	9'-2 7⁄16"	8'-8 5⁄8"	3'-5 1⁄8"	19'-2 5⁄8"	6'-11 1⁄8"	20'-8 5⁄8"	7'-5 1⁄8"				
9'-6"	9'-10 3⁄4"	9'-8 7⁄16"	9'-2 5⁄8"	3'-7 1⁄8"	18'-2 5⁄8"	6'-7 1⁄8"						
10'-0"	10'-4 3⁄4"	10'-2 7⁄16"	9'-8 5⁄8"	3'-9 1⁄8"	17'-8 5⁄8"	6'-5 1⁄8"						
10'-6"	10'-10 3⁄4"	10'-8 7⁄16"	10'-2 5⁄8"	3'-11 1⁄8"	16'-8 5⁄8"	6'-1 1⁄8"						
11'-0"	11'-4 3⁄4"	11'-2 7⁄16"	10'-8 5⁄8"	4'-1 1⁄8"	15'-11 5⁄8"	5'-10 1⁄8"						
11'-6"	11'-10 3⁄4"	11'-8 7⁄16"	11'-2 5⁄8"	4'-3 1⁄8"	15'-2 5⁄8"	5'-7 1⁄8"	20'-8 5⁄8"	7'-5 1⁄8"				
12'-0"	12'-4 3⁄4"	12'-2 7⁄16"	11'-8 5⁄8"	4'-5 1⁄8"	14'-8 5⁄8"	5'-5 1⁄8"						
> 12'-0"		Contact local Andersen supplier										

## Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications.  
Dimensions in parentheses are in millimeters.

Date: 7/11/18  
Scale: None




Chart 4.0		One-Directional - Four Panel										
Lock Jamb Depth = 11'11 <sup>15</sup> / <sub>16</sub> ", O.A. Frame Depth = 1'-10'13 <sup>15</sup> / <sub>16</sub> ", Pocket Depth = 2'-0'9 <sup>15</sup> / <sub>16</sub> "												
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width							
			R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.		
			Rated				Not Rated					
Without Intermediate Stile						With Intermediate Stile						
Contact local Andersen supplier												
< 6'-6"												
6'-6"	6'-10 3/4"	6'-8 7/16"	8'-1 1/8"	2'-7 1/8"	27'-5 1/8"	7'-5 1/8"	47'-3 1/8"	12'-5 1/8"	Contact local Andersen supplier	Contact local Andersen supplier		
7'-0"	7'-4 3/4"	7'-2 7/16"	8'-9 1/8"	2'-9 1/8"								
7'-6"	7'-10 3/4"	7'-8 7/16"	9'-5 1/8"	2'-11 1/8"								
8'-0"	8'-4 3/4"	8'-2 7/16"	10'-1 1/8"	3'-1 1/8"								
8'-6"	8'-10 3/4"	8'-8 7/16"	10'-9 1/8"	3'-3 1/8"								
9'-0"	9'-4 3/4"	9'-2 7/16"	11'-5 1/8"	3'-5 1/8"	25'-5 1/8"	6'-11 1/8"	27'-5 1/8"	7'-5 1/8"				
9'-6"	9'-10 3/4"	9'-8 7/16"	12'-1 1/8"	3'-7 1/8"	24'-1 1/8"	6'-7 1/8"						
10'-0"	10'-4 3/4"	10'-2 7/16"	12'-9 1/8"	3'-9 1/8"	23'-5 1/8"	6'-5 1/8"						
10'-6"	10'-10 3/4"	10'-8 7/16"	13'-5 1/8"	3'-11 1/8"	22'-1 1/8"	6'-1 1/8"						
11'-0"	11'-4 3/4"	11'-2 7/16"	14'-1 1/8"	4'-1 1/8"	21'-1 1/8"	5'-10 1/8"						
11'-6"	11'-10 3/4"	11'-8 7/16"	14'-9 1/8"	4'-3 1/8"	20'-1 1/8"	5'-7 1/8"						
12'-0"	12'-4 3/4"	12'-2 7/16"	15'-5 1/8"	4'-5 1/8"	19'-3 1/8"	5'-5 1/8"						
> 12'-0"					Contact local Andersen supplier							

Chart 4.1		One-Directional - Five Panel											
Lock Jamb Depth = 1'-1 9/16", O.A. Frame Depth = 2'-4 3/8", Pocket Depth = 2'-6 1/8"													
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width								
			R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.			
			Rated				Not Rated						
		Without Intermediate Stile							With Intermediate Stile				
< 6'-6"		Contact local Andersen supplier											
6'-6"	6'-10 3/4"	6'-8 7/16"	9'-11 5/8"	2'-7 1/8"	34'-1 5/8"	7'-5 1/8"	59'-1 5/8"	12'-5 1/8"	Contact local Andersen supplier	Contact local Andersen supplier			
7'-0"	7'-4 3/4"	7'-2 7/16"	10'-9 5/8"	2'-9 1/8"			34'-1 5/8"	7'-5 1/8"					
7'-6"	7'-10 3/4"	7'-8 7/16"	11'-7 5/8"	2'-11 1/8"									
8'-0"	8'-4 3/4"	8'-2 7/16"	12'-5 5/8"	3'-1 1/8"									
8'-6"	8'-10 3/4"	8'-8 7/16"	13'-3 5/8"	3'-3 1/8"									
9'-0"	9'-4 3/4"	9'-2 7/16"	14'-1 5/8"	3'-5 1/8"	31'-7 5/8"	6'-11 1/8"	34'-1 5/8"	7'-5 1/8"					
9'-6"	9'-10 3/4"	9'-8 7/16"	14'-11 5/8"	3'-7 1/8"	29'-11 5/8"	6'-7 1/8"							
10'-0"	10'-4 3/4"	10'-2 7/16"	15'-9 5/8"	3'-9 1/8"	29'-1 5/8"	6'-5 1/8"							
10'-6"	10'-10 3/4"	10'-8 7/16"	16'-7 5/8"	3'-11 1/8"	27'-5 5/8"	6'-1 1/8"							
11'-0"	11'-4 3/4"	11'-2 7/16"	17'-5 5/8"	4'-1 1/8"	26'-2 5/8"	5'-10 1/8"							
11'-6"	11'-10 3/4"	11'-8 7/16"	18'-3 5/8"	4'-3 1/8"	24'-11 5/8"	5'-7 1/8"							
12'-0"	12'-4 3/4"	12'-2 7/16"	19'-1 5/8"	4'-5 1/8"	24'-1 5/8"	5'-5 1/8"							
> 12'-0"		Contact local Andersen supplier											

Chart 4.2		One-Directional - Six Panel										
Lock Jamb Depth = 1'-3 3/8", O.A. Frame Depth = 2'-9 7/8", Pocket Depth = 2'-11 5/8"												
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width							
			R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.		
			Rated		Not Rated							
		Without Intermediate Stile							With Intermediate Stile			
< 6'-6"		Contact local Andersen supplier										
6'-6"	6'-10 3/4"	6'-8 7/16"	11'-10 1/8"	2'-7 1/8"	40'-10 1/8"	7'-5 1/8"	70'-10 1/8"	12'-5 1/8"	Contact local Andersen supplier	Contact local Andersen supplier		
7'-0"	7'-4 3/4"	7'-2 7/16"	12'-10 1/8"	2'-9 1/8"			40'-10 1/8"	7'-5 1/8"				
7'-6"	7'-10 3/4"	7'-8 7/16"	13'-10 1/8"	2'-11 1/8"								
8'-0"	8'-4 3/4"	8'-2 7/16"	14'-10 1/8"	3'-1 1/8"								
8'-6"	8'-10 3/4"	8'-8 7/16"	15'-10 1/8"	3'-3 1/8"								
9'-0"	9'-4 3/4"	9'-2 7/16"	16'-10 1/8"	3'-5 1/8"	37'-10 1/8"	6'-11 1/8"	40'-10 1/8"	7'-5 1/8"				
9'-6"	9'-10 3/4"	9'-8 7/16"	17'-10 1/8"	3'-7 1/8"	35'-10 1/8"	6'-7 1/8"						
10'-0"	10'-4 3/4"	10'-2 7/16"	18'-10 1/8"	3'-9 1/8"	34'-10 1/8"	6'-5 1/8"						
10'-6"	10'-10 3/4"	10'-8 7/16"	19'-10 1/8"	3'-11 1/8"	32'-10 1/8"	6'-1 1/8"						
11'-0"	11'-4 3/4"	11'-2 7/16"	20'-10 1/8"	4'-1 1/8"	31'-4 1/8"	5'-10 1/8"						
11'-6"	11'-10 3/4"	11'-8 7/16"	21'-10 1/8"	4'-3 1/8"	29'-10 1/8"	5'-7 1/8"						
12'-0"	12'-4 3/4"	12'-2 7/16"	22'-10 1/8"	4'-5 1/8"	28'-10 1/8"	5'-5 1/8"						
> 12'-0"	Contact local Andersen supplier											

## Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications.  
Dimensions in parentheses are in millimeters.

Date: 7/11/18  
Scale: None

Chart 5.0			Two-Directional - Two Panel									
Frame Depth = 6 ¼", Pocket Depth = 8"												
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width							
			R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.		
			Rated			Not Rated						
			Without Intermediate Stile						With Intermediate Stile			
Contact local Andersen supplier												
< 6'-6"												
6'-6"	6'-10 ¾"	6'-8 ⅞"	4'-7 ⅞"	2'-7 ⅞"	14'-3 ⅞"	7'-5 ⅞"	24'-3 ⅞"	12'-5 ⅞"	Contact local Andersen supplier	Contact local Andersen supplier		
7'-0"	7'-4 ¾"	7'-2 ⅞"	4'-11 ⅞"	2'-9 ⅞"								
7'-6"	7'-10 ¾"	7'-8 ⅞"	5'-3 ⅞"	2'-11 ⅞"								
8'-0"	8'-4 ¾"	8'-2 ⅞"	5'-7 ⅞"	3'-1 ⅞"								
8'-6"	8'-10 ¾"	8'-8 ⅞"	5'-11 ⅞"	3'-3 ⅞"								
9'-0"	9'-4 ¾"	9'-2 ⅞"	6'-3 ⅞"	3'-5 ⅞"	13'-3 ⅞"	6'-11 ⅞"	14'-3 ⅞"	7'-5 ⅞"				
9'-6"	9'-10 ¾"	9'-8 ⅞"	6'-7 ⅞"	3'-7 ⅞"	12'-7 ⅞"	6'-7 ⅞"						
10'-0"	10'-4 ¾"	10'-2 ⅞"	6'-11 ⅞"	3'-9 ⅞"	12'-3 ⅞"	6'-5 ⅞"						
10'-6"	10'-10 ¾"	10'-8 ⅞"	7'-3 ⅞"	3'-11 ⅞"	11'-7 ⅞"	6'-1 ⅞"						
11'-0"	11'-4 ¾"	11'-2 ⅞"	7'-7 ⅞"	4'-1 ⅞"	11'-1 ⅞"	5'-10 ⅞"						
11'-6"	11'-10 ¾"	11'-8 ⅞"	7'-11 ⅞"	4'-3 ⅞"	10'-7 ⅞"	5'-7 ⅞"						
12'-0"	12'-4 ¾"	12'-2 ⅞"	8'-3 ⅞"	4'-5 ⅞"	10'-3 ⅞"	5'-5 ⅞"						
> 12'-0"			Contact local Andersen supplier									






Chart 5.1		Two-Directional - Four Panel										
Head Jamb Depth at Astragal = 8 1/16", O.A. Frame Depth = 11 3/4", Pocket Depth = 1'-1 9/16"												
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width							
			R.O.	Pocket R.O.	R.O.		Pocket R.O.		R.O.		Pocket R.O.	
			Rated				Not Rated					
					Without Intermediate Stile						With Intermediate Stile	
Contact local Andersen supplier												
< 6'-6"												
6'-6"	6'-10 3/4"	6'-8 7/16"	8'-4 7/16"	2'-7 1/8"	27'-8 7/16"	7'-5 1/8"	47'-6 7/16"	12'-5 1/8"	Contact local Andersen supplier	Contact local Andersen supplier		
7'-0"	7'-4 3/4"	7'-2 7/16"	9'-0 7/16"	2'-9 1/8"								
7'-6"	7'-10 3/4"	7'-8 7/16"	9'-8 7/16"	2'-11 1/8"								
8'-0"	8'-4 3/4"	8'-2 7/16"	10'-4 7/16"	3'-1 1/8"								
8'-6"	8'-10 3/4"	8'-8 7/16"	11'-0 7/16"	3'-3 3/8"								
9'-0"	9'-4 3/4"	9'-2 7/16"	11'-8 7/16"	3'-5 3/8"			25'-8 7/16"	6'-11 1/8"				
9'-6"	9'-10 3/4"	9'-8 7/16"	12'-4 7/16"	3'-7 3/8"			24'-4 7/16"	6'-7 3/8"				
10'-0"	10'-4 3/4"	10'-2 7/16"	13'-0 7/16"	3'-9 3/8"			23'-8 7/16"	6'-5 1/8"				
10'-6"	10'-10 3/4"	10'-8 7/16"	13'-8 7/16"	3'-11 1/8"	22'-4 7/16"	6'-1 1/8"	27'-8 7/16"	7'-5 1/8"	Contact local Andersen supplier	Contact local Andersen supplier		
11'-0"	11'-4 3/4"	11'-2 7/16"	14'-4 7/16"	4'-1 3/8"	21'-4 7/16"	5'-10 1/8"						
11'-6"	11'-10 3/4"	11'-8 7/16"	15'-0 7/16"	4'-3 3/8"	20'-4 7/16"	5'-7 1/8"						
12'-0"	12'-4 3/4"	12'-2 7/16"	15'-8 7/16"	4'-5 1/8"	19'-6 7/16"	5'-5 1/8"						
> 12'-0"					Contact local Andersen supplier							

Chart 5.2		Two-Directional - Six Panel												
Head Jamb Depth at Astragal = 9 7/8", O.A. Frame Depth = 1'-5 5/16", Pocket Depth = 1'-7 1/16"														
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width									
			R.O.	Pocket R.O.	R.O.		Pocket R.O.		R.O.	Pocket R.O.	R.O.	Pocket R.O.		
			Rated				Not Rated							
			Without Intermediate Stile								With Intermediate Stile			
Contact local Andersen supplier														
< 6'-6"														
6'-6"	6'-10 3/4"	6'-8 7/16"	12'-1 7/16"	2'-7 1/8"	41'-1 7/16"	7'-5 1/8"	71'-1 7/16"	12'-5 1/8"	Contact local Andersen supplier	Contact local Andersen supplier				
7'-0"	7'-4 3/4"	7'-2 7/16"	13'-1 7/16"	2'-9 1/8"										
7'-6"	7'-10 3/4"	7'-8 7/16"	14'-1 7/16"	2'-11 1/8"			41'-1 7/16"	7'-5 1/8"						
8'-0"	8'-4 3/4"	8'-2 7/16"	15'-1 7/16"	3'-1 1/8"										
8'-6"	8'-10 3/4"	8'-8 7/16"	16'-1 7/16"	3'-3 3/8"										
9'-0"	9'-4 3/4"	9'-2 7/16"	17'-1 7/16"	3'-5 1/8"										
9'-6"	9'-10 3/4"	9'-8 7/16"	18'-1 7/16"	3'-7 1/8"										
10'-0"	10'-4 3/4"	10'-2 7/16"	19'-1 7/16"	3'-9 1/8"										
10'-6"	10'-10 3/4"	10'-8 7/16"	20'-1 7/16"	3'-11 1/8"										
11'-0"	11'-4 3/4"	11'-2 7/16"	21'-1 7/16"	4'-1 1/8"										
11'-6"	11'-10 3/4"	11'-8 7/16"	22'-1 7/16"	4'-3 3/8"										
12'-0"	12'-4 3/4"	12'-2 7/16"	23'-1 7/16"	4'-5 1/8"										
> 12'-0"														
Contact local Andersen supplier														

## Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications.  
Dimensions in parentheses are in millimeters.

Date: 7/11/18  
Scale: None

Chart 6.0		Two-Directional - Eight Panel									
Head Jamb Depth at Astragal = 11 <sup>11</sup> / <sub>16</sub> ", O.A. Frame Depth = 1'-10 <sup>13</sup> / <sub>16</sub> ", Pocket Depth = 2'-0 <sup>9</sup> / <sub>16</sub> "											
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width						
			R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	
			Rated				Not Rated				
			Without Intermediate Stile					With Intermediate Stile			
Contact local Andersen supplier											
< 6'-6"											
6'-6"	6'-10 <sup>3</sup> / <sub>4</sub> "	6'-8 <sup>7</sup> / <sub>16</sub> "	15'-10 <sup>7</sup> / <sub>16</sub> "	2'-7 <sup>1</sup> / <sub>8</sub> "	43'-9 <sup>3</sup> / <sub>4</sub> "	6'-1"	94'-6 <sup>7</sup> / <sub>16</sub> "	12'-5 <sup>1</sup> / <sub>8</sub> "	Contact local Andersen supplier	Contact local Andersen supplier	
7'-0"	7'-4 <sup>3</sup> / <sub>4</sub> "	7'-2 <sup>7</sup> / <sub>16</sub> "	17'-2 <sup>7</sup> / <sub>16</sub> "	2'-9 <sup>1</sup> / <sub>8</sub> "			54'-6 <sup>7</sup> / <sub>16</sub> "	7'-5 <sup>1</sup> / <sub>8</sub> "			
7'-6"	7'-10 <sup>3</sup> / <sub>4</sub> "	7'-8 <sup>7</sup> / <sub>16</sub> "	18'-6 <sup>7</sup> / <sub>16</sub> "	2'-11 <sup>1</sup> / <sub>8</sub> "							
8'-0"	8'-4 <sup>3</sup> / <sub>4</sub> "	8'-2 <sup>7</sup> / <sub>16</sub> "	19'-10 <sup>7</sup> / <sub>16</sub> "	3'-1 <sup>1</sup> / <sub>8</sub> "							
8'-6"	8'-10 <sup>3</sup> / <sub>4</sub> "	8'-8 <sup>7</sup> / <sub>16</sub> "	21'-2 <sup>7</sup> / <sub>16</sub> "	3'-3 <sup>1</sup> / <sub>8</sub> "							
9'-0"	9'-4 <sup>3</sup> / <sub>4</sub> "	9'-2 <sup>7</sup> / <sub>16</sub> "	22'-6 <sup>7</sup> / <sub>16</sub> "	3'-5 <sup>1</sup> / <sub>8</sub> "							
9'-6"	9'-10 <sup>3</sup> / <sub>4</sub> "	9'-8 <sup>7</sup> / <sub>16</sub> "	23'-10 <sup>7</sup> / <sub>16</sub> "	3'-7 <sup>1</sup> / <sub>8</sub> "							
10'-0"	10'-4 <sup>3</sup> / <sub>4</sub> "	10'-2 <sup>7</sup> / <sub>16</sub> "	25'-2 <sup>7</sup> / <sub>16</sub> "	3'-9 <sup>1</sup> / <sub>8</sub> "							
10'-6"	10'-10 <sup>3</sup> / <sub>4</sub> "	10'-8 <sup>7</sup> / <sub>16</sub> "	26'-6 <sup>7</sup> / <sub>16</sub> "	3'-11 <sup>1</sup> / <sub>8</sub> "							
11'-0"	11'-4 <sup>3</sup> / <sub>4</sub> "	11'-2 <sup>7</sup> / <sub>16</sub> "	27'-10 <sup>7</sup> / <sub>16</sub> "	4'-1 <sup>1</sup> / <sub>8</sub> "							41'-10 <sup>7</sup> / <sub>16</sub> "
11'-6"	11'-10 <sup>3</sup> / <sub>4</sub> "	11'-8 <sup>7</sup> / <sub>16</sub> "	29'-2 <sup>7</sup> / <sub>16</sub> "	4'-3 <sup>1</sup> / <sub>8</sub> "	39'-10 <sup>7</sup> / <sub>16</sub> "	5'-7 <sup>1</sup> / <sub>8</sub> "					
12'-0"	12'-4 <sup>3</sup> / <sub>4</sub> "	12'-2 <sup>7</sup> / <sub>16</sub> "	30'-6 <sup>7</sup> / <sub>16</sub> "	4'-5 <sup>1</sup> / <sub>8</sub> "	38'-6 <sup>7</sup> / <sub>16</sub> "	5'-5 <sup>1</sup> / <sub>8</sub> "					
> 12'-0"			Contact local Andersen supplier								






Chart 6.1		Two-Directional - Ten Panel											
Head Jamb Depth at Astragal = 1'-1 9/16", O.A. Frame Depth = 2'-4 3/8", Pocket Depth = 2'-6 1/8"													
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width								
			R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.			
			Rated			Not Rated							
Without Intermediate Stile												With Intermediate Stile	
Contact local Andersen supplier													
< 6'-6"													
6'-6"	6'-10 3/4"	6'-8 7/16"	19'-7 7/16"	2'-7 1/8"	43'-9 3/4"	5'-0 1/8"	117'-11 7/16"	12'-5 1/8"	Contact local Andersen supplier	Contact local Andersen supplier			
7'-0"	7'-4 3/4"	7'-2 7/16"	21'-3 7/16"	2'-9 1/8"									
7'-6"	7'-10 3/4"	7'-8 7/16"	22'-11 7/16"	2'-11 1/8"									
8'-0"	8'-4 3/4"	8'-2 7/16"	24'-7 7/16"	3'-1 1/8"									
8'-6"	8'-10 3/4"	8'-8 7/16"	26'-3 7/16"	3'-3 1/8"									
9'-0"	9'-4 3/4"	9'-2 7/16"	27'-11 7/16"	3'-5 1/8"									
9'-6"	9'-10 3/4"	9'-8 7/16"	29'-7 7/16"	3'-7 1/8"									
10'-0"	10'-4 3/4"	10'-2 7/16"	31'-3 7/16"	3'-9 1/8"									
10'-6"	10'-10 3/4"	10'-8 7/16"	32'-11 7/16"	3'-11 1/8"									
11'-0"	11'-4 3/4"	11'-2 7/16"	34'-7 7/16"	4'-1 1/8"									
11'-6"	11'-10 3/4"	11'-8 7/16"	36'-3 7/16"	4'-3 1/8"									
12'-0"	12'-4 3/4"	12'-2 7/16"	37'-11 7/16"	4'-5 1/8"									
> 12'-0"					Contact local Andersen supplier								

Chart 6.2		Two-Directional - Twelve Panel									
Head Jamb Depth at Astragal = 1'-3 3⁄8", O.A. Frame Depth = 2'-9 7⁄8", Pocket Depth = 2'-11 5⁄8"											
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width						
			R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	
			Rated				Not Rated				
			Without Intermediate Stile						With Intermediate Stile		
< 6'-6"		Contact local Andersen supplier									
6'-6"	6'-10 3⁄4"	6'-8 7⁄16"	23'-4 7⁄16"	2'-7 1⁄8"	43'-9 3⁄4"	4'-3 9⁄16"	141'-4 7⁄16"	12'-5 1⁄8"	Contact local Andersen supplier	Contact local Andersen supplier	
7'-0"	7'-4 3⁄4"	7'-2 7⁄16"	25'-4 7⁄16"	2'-9 1⁄8"							
7'-6"	7'-10 3⁄4"	7'-8 7⁄16"	27'-4 7⁄16"	2'-11 1⁄8"							
8'-0"	8'-4 3⁄4"	8'-2 7⁄16"	29'-4 7⁄16"	3'-1 1⁄8"							
8'-6"	8'-10 3⁄4"	8'-8 7⁄16"	31'-4 7⁄16"	3'-3 1⁄8"							
9'-0"	9'-4 3⁄4"	9'-2 7⁄16"	33'-4 7⁄16"	3'-5 1⁄8"							
9'-6"	9'-10 3⁄4"	9'-8 7⁄16"	35'-4 7⁄16"	3'-7 1⁄8"							
10'-0"	10'-4 3⁄4"	10'-2 7⁄16"	37'-4 7⁄16"	3'-9 1⁄8"							
10'-6"	10'-10 3⁄4"	10'-8 7⁄16"	39'-4 7⁄16"	3'-11 1⁄8"							
11'-0"	11'-4 3⁄4"	11'-2 7⁄16"	41'-4 7⁄16"	4'-1 1⁄8"							
11'-6"	11'-10 3⁄4"	11'-8 7⁄16"	43'-4 7⁄16"	4'-3 1⁄8"							
12'-0"	12'-4 3⁄4"	12'-2 7⁄16"	45'-4 7⁄16"	4'-5 1⁄8"							
> 12'-0"		Contact local Andersen supplier									

## Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications.  
Dimensions in parentheses are in millimeters.

Date: 7/11/18  
Scale: None