







Big Doors

Weiland™ Pocket Liftslide
Aluminum Wood - No Screen









Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications.
Dimensions in parentheses are in millimeters.

Date: 7/11/18
Scale: None

Big Doors

Weiland™ Pocket Liftslide
Aluminum Wood - No Screen



Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications.
Dimensions in parentheses are in millimeters.

Date: 7/11/18
Scale: None

Chart 3.0		One-Directional - One Panel										
Frame Depth = 3 5/16", Pocket Depth = 5 5/16"												
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width							
			R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.		
			Rated				Not Rated					
Without Intermediate Stile						With Intermediate Stile						
Contact local Andersen supplier												
< 6'-6"												
6'-6"	6'-10 3/4"	6'-8 7/16"	2'-5 5/8"	2'-7 1/8"	7'-3 5/8"	7'-5 1/8"	12'-3 5/8"	12'-5 1/8"	Contact local Andersen supplier	Contact local Andersen supplier		
7'-0"	7'-4 3/4"	7'-2 7/16"	2'-7 5/8"	2'-9 1/8"								
7'-6"	7'-10 3/4"	7'-8 7/16"	2'-9 5/8"	2'-11 1/8"								
8'-0"	8'-4 3/4"	8'-2 7/16"	2'-11 5/8"	3'-1 1/8"								
8'-6"	8'-10 3/4"	8'-8 7/16"	3'-1 5/8"	3'-3 1/8"								
9'-0"	9'-4 3/4"	9'-2 7/16"	3'-3 5/8"	3'-5 1/8"	6'-9 5/8"	6'-11 1/8"	7'-3 5/8"	7'-5 1/8"				
9'-6"	9'-10 3/4"	9'-8 7/16"	3'-5 5/8"	3'-7 1/8"	6'-5 5/8"	6'-7 1/8"						
10'-0"	10'-4 3/4"	10'-2 7/16"	3'-7 5/8"	3'-9 1/8"	6'-3 5/8"	6'-5 1/8"						
10'-6"	10'-10 3/4"	10'-8 7/16"	3'-9 5/8"	3'-11 1/8"	5'-11 5/8"	6'-1 1/8"						
11'-0"	11'-4 3/4"	11'-2 7/16"	3'-11 5/8"	4'-1 1/8"	5'-8 5/8"	5'-10 1/8"						
11'-6"	11'-10 3/4"	11'-8 7/16"	4'-1 5/8"	4'-3 1/8"	5'-5 5/8"	5'-7 1/8"						
12'-0"	12'-4 3/4"	12'-2 7/16"	4'-3 5/8"	4'-5 1/8"	5'-3 5/8"	5'-5 1/8"						
> 12'-0"												
Contact local Andersen supplier												






Chart 3.1		One-Directional - Two Panel											
Lock Jamb Depth = 3 9/16", O.A. Frame Depth = 7 1/4", Pocket Depth = 9"													
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width								
			R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.			
			Rated				Not Rated						
			Without Intermediate Stile						With Intermediate Stile				
< 6'-6"		Contact local Andersen supplier											
6'-6"	6'-10 3/4"	6'-8 7/16"	4'-4 1/8"	2'-7 1/8"	14'-0 1/8"	7'-5 1/8"	24'-0 1/8"	12'-5 1/8"	Contact local Andersen supplier	Contact local Andersen supplier			
7'-0"	7'-4 3/4"	7'-2 7/16"	4'-8 1/8"	2'-9 1/8"			14'-0 1/8"	7'-5 1/8"					
7'-6"	7'-10 3/4"	7'-8 7/16"	5'-0 1/8"	2'-11 1/8"									
8'-0"	8'-4 3/4"	8'-2 7/16"	5'-4 1/8"	3'-1 1/8"									
8'-6"	8'-10 3/4"	8'-8 7/16"	5'-8 1/8"	3'-3 1/8"									
9'-0"	9'-4 3/4"	9'-2 7/16"	6'-0 1/8"	3'-5 1/8"	13'-0 1/8"	6'-11 1/8"	14'-0 1/8"	7'-5 1/8"					
9'-6"	9'-10 3/4"	9'-8 7/16"	6'-4 1/8"	3'-7 1/8"	12'-4 1/8"	6'-7 1/8"							
10'-0"	10'-4 3/4"	10'-2 7/16"	6'-8 1/8"	3'-9 1/8"	12'-0 1/8"	6'-5 1/8"							
10'-6"	10'-10 3/4"	10'-8 7/16"	7'-0 1/8"	3'-11 1/8"	11'-4 1/8"	6'-1 1/8"							
11'-0"	11'-4 3/4"	11'-2 7/16"	7'-4 1/8"	4'-1 1/8"	10'-10 1/8"	5'-10 1/8"							
11'-6"	11'-10 3/4"	11'-8 7/16"	7'-8 1/8"	4'-3 1/8"	10'-4 1/8"	5'-7 1/8"	14'-0 1/8"	7'-5 1/8"					
12'-0"	12'-4 3/4"	12'-2 7/16"	8'-0 1/8"	4'-5 1/8"	10'-0 1/8"	5'-5 1/8"							
> 12'-0"		Contact local Andersen supplier											

Chart 3.2		One-Directional - Three Panel											
Lock Jamb Depth = 3 ⁹ / ₁₆ " , O.A. Frame Depth = 10 ¹⁵ / ₁₆ " , Pocket Depth = 1'-0 ¹¹ / ₁₆ "													
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width								
			R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.			
			Rated				Not Rated						
			Without Intermediate Stile						With Intermediate Stile				
< 6'-6"		Contact local Andersen supplier											
6'-6"	6'-10 ³ / ₄ "	6'-8 ⁷ / ₁₆ "	6'-2 ⁵ / ₈ "	2'-7 ¹ / ₈ "	20'-8 ⁵ / ₈ "	7'-5 ¹ / ₈ "	35'-8 ⁵ / ₈ "	12'-5 ¹ / ₈ "	Contact local Andersen supplier	Contact local Andersen supplier			
7'-0"	7'-4 ³ / ₄ "	7'-2 ⁷ / ₁₆ "	6'-8 ⁵ / ₈ "	2'-9 ¹ / ₈ "			20'-8 ⁵ / ₈ "	7'-5 ¹ / ₈ "					
7'-6"	7'-10 ³ / ₄ "	7'-8 ⁷ / ₁₆ "	7'-2 ⁵ / ₈ "	2'-11 ¹ / ₈ "									
8'-0"	8'-4 ³ / ₄ "	8'-2 ⁷ / ₁₆ "	7'-8 ⁵ / ₈ "	3'-1 ¹ / ₈ "									
8'-6"	8'-10 ³ / ₄ "	8'-8 ⁷ / ₁₆ "	8'-2 ⁵ / ₈ "	3'-3 ¹ / ₈ "									
9'-0"	9'-4 ³ / ₄ "	9'-2 ⁷ / ₁₆ "	8'-8 ⁵ / ₈ "	3'-5 ¹ / ₈ "	19'-2 ⁵ / ₈ "	6'-11 ¹ / ₈ "	20'-8 ⁵ / ₈ "	7'-5 ¹ / ₈ "					
9'-6"	9'-10 ³ / ₄ "	9'-8 ⁷ / ₁₆ "	9'-2 ⁵ / ₈ "	3'-7 ¹ / ₈ "	18'-2 ⁵ / ₈ "	6'-7 ¹ / ₈ "							
10'-0"	10'-4 ³ / ₄ "	10'-2 ⁷ / ₁₆ "	9'-8 ⁵ / ₈ "	3'-9 ¹ / ₈ "	17'-8 ⁵ / ₈ "	6'-5 ¹ / ₈ "							
10'-6"	10'-10 ³ / ₄ "	10'-8 ⁷ / ₁₆ "	10'-2 ⁵ / ₈ "	3'-11 ¹ / ₈ "	16'-8 ⁵ / ₈ "	6'-1 ¹ / ₈ "							
11'-0"	11'-4 ³ / ₄ "	11'-2 ⁷ / ₁₆ "	10'-8 ⁵ / ₈ "	4'-1 ¹ / ₈ "	15'-11 ⁵ / ₈ "	5'-10 ¹ / ₈ "							
11'-6"	11'-10 ³ / ₄ "	11'-8 ⁷ / ₁₆ "	11'-2 ⁵ / ₈ "	4'-3 ¹ / ₈ "	15'-2 ⁵ / ₈ "	5'-7 ¹ / ₈ "	20'-8 ⁵ / ₈ "	7'-5 ¹ / ₈ "					
12'-0"	12'-4 ³ / ₄ "	12'-2 ⁷ / ₁₆ "	11'-8 ⁵ / ₈ "	4'-5 ¹ / ₈ "	14'-8 ⁵ / ₈ "	5'-5 ¹ / ₈ "							
> 12'-0"		Contact local Andersen supplier											

Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications.
Dimensions in parentheses are in millimeters.

Date: 7/11/18
Scale: None




Chart 4.0		One-Directional - Four Panel										
Lock Jamb Depth = 3 9/16", O.A. Frame Depth = 1'-2 11/16", Pocket Depth = 1'-4 7/16"												
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width							
			R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.		
			Rated				Not Rated					
Without Intermediate Stile								With Intermediate Stile				
Contact local Andersen supplier												
< 6'-6"												
6'-6"	6'-10 3/4"	6'-8 7/16"	8'-1 1/8"	2'-7 1/8"	27'-5 1/8"	7'-5 1/8"	47'-3 1/8"	12'-5 1/8"	Contact local Andersen supplier	Contact local Andersen supplier		
7'-0"	7'-4 3/4"	7'-2 7/16"	8'-9 1/8"	2'-9 1/8"								
7'-6"	7'-10 3/4"	7'-8 7/16"	9'-5 1/8"	2'-11 1/8"								
8'-0"	8'-4 3/4"	8'-2 7/16"	10'-1 1/8"	3'-1 1/8"								
8'-6"	8'-10 3/4"	8'-8 7/16"	10'-9 1/8"	3'-3 1/8"								
9'-0"	9'-4 3/4"	9'-2 7/16"	11'-5 1/8"	3'-5 1/8"	25'-5 1/8"	6'-11 1/8"	27'-5 1/8"	7'-5 1/8"				
9'-6"	9'-10 3/4"	9'-8 7/16"	12'-1 1/8"	3'-7 1/8"	24'-1 1/8"	6'-7 1/8"						
10'-0"	10'-4 3/4"	10'-2 7/16"	12'-9 1/8"	3'-9 1/8"	23'-5 1/8"	6'-5 1/8"						
10'-6"	10'-10 3/4"	10'-8 7/16"	13'-5 1/8"	3'-11 1/8"	22'-1 1/8"	6'-1 1/8"						
11'-0"	11'-4 3/4"	11'-2 7/16"	14'-1 1/8"	4'-1 1/8"	21'-1 1/8"	5'-10 1/8"						
11'-6"	11'-10 3/4"	11'-8 7/16"	14'-9 1/8"	4'-3 1/8"	20'-1 1/8"	5'-7 1/8"						
12'-0"	12'-4 3/4"	12'-2 7/16"	15'-5 1/8"	4'-5 1/8"	19'-3 1/8"	5'-5 1/8"						
> 12'-0"					Contact local Andersen supplier							

Chart 4.1		One-Directional - Five Panel									
Lock Jamb Depth = 3 9/16", O.A. Frame Depth = 1'-6 3/8", Pocket Depth = 1'-8 1/8"											
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width						
			R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	
			Rated				Not Rated				
			Without Intermediate Stile						With Intermediate Stile		
< 6'-6"		Contact local Andersen supplier									
6'-6"	6'-10 3/4"	6'-8 7/16"	9'-11 5/8"	2'-7 1/8"	34'-1 5/8"	7'-5 1/8"	59'-1 5/8"	12'-5 1/8"	Contact local Andersen supplier	Contact local Andersen supplier	
7'-0"	7'-4 3/4"	7'-2 7/16"	10'-9 5/8"	2'-9 1/8"			34'-1 5/8"	7'-5 1/8"			
7'-6"	7'-10 3/4"	7'-8 7/16"	11'-7 5/8"	2'-11 1/8"							
8'-0"	8'-4 3/4"	8'-2 7/16"	12'-5 5/8"	3'-1 1/8"							
8'-6"	8'-10 3/4"	8'-8 7/16"	13'-3 5/8"	3'-3 1/8"							
9'-0"	9'-4 3/4"	9'-2 7/16"	14'-1 5/8"	3'-5 1/8"							
9'-6"	9'-10 3/4"	9'-8 7/16"	14'-11 5/8"	3'-7 1/8"	31'-7 5/8"	6'-11 1/8"					
10'-0"	10'-4 3/4"	10'-2 7/16"	15'-9 5/8"	3'-9 1/8"	29'-11 5/8"	6'-7 1/8"					
10'-6"	10'-10 3/4"	10'-8 7/16"	16'-7 5/8"	3'-11 1/8"	29'-1 5/8"	6'-5 1/8"					
11'-0"	11'-4 3/4"	11'-2 7/16"	17'-5 5/8"	4'-1 1/8"	27'-5 5/8"	6'-1 1/8"					
11'-6"	11'-10 3/4"	11'-8 7/16"	18'-3 5/8"	4'-3 1/8"	26'-2 5/8"	5'-10 1/8"					
12'-0"	12'-4 3/4"	12'-2 7/16"	19'-1 5/8"	4'-5 1/8"	24'-11 5/8"	5'-7 1/8"					
12'-6"	12'-8 3/4"	12'-2 7/16"	19'-1 5/8"	4'-5 1/8"	24'-1 5/8"	5'-5 1/8"					
> 12'-0"	Contact local Andersen supplier										

Chart 4.2		One-Directional - Six Panel										
Lock Jamb Depth = 3 9⁄16", O.A. Frame Depth = 1'-10 1⁄16", Pocket Depth = 1'-11 13⁄16"												
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width							
			R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.		
			Rated				Not Rated					
			Without Intermediate Stile						With Intermediate Stile			
< 6'-6"		Contact local Andersen supplier										
6'-6"	6'-10 3⁄4"	6'-8 7⁄16"	11'-10 1⁄8"	2'-7 1⁄8"	40'-10 1⁄8"	7'-5 1⁄8"	70'-10 1⁄8"	12'-5 1⁄8"	Contact local Andersen supplier	Contact local Andersen supplier		
7'-0"	7'-4 3⁄4"	7'-2 7⁄16"	12'-10 1⁄8"	2'-9 1⁄8"								
7'-6"	7'-10 3⁄4"	7'-8 7⁄16"	13'-10 1⁄8"	2'-11 1⁄8"								
8'-0"	8'-4 3⁄4"	8'-2 7⁄16"	14'-10 1⁄8"	3'-1 1⁄8"								
8'-6"	8'-10 3⁄4"	8'-8 7⁄16"	15'-10 1⁄8"	3'-3 1⁄8"								
9'-0"	9'-4 3⁄4"	9'-2 7⁄16"	16'-10 1⁄8"	3'-5 1⁄8"			37'-10 1⁄8"	6'-11 1⁄8"				
9'-6"	9'-10 3⁄4"	9'-8 7⁄16"	17'-10 1⁄8"	3'-7 1⁄8"			35'-10 1⁄8"	6'-7 1⁄8"				
10'-0"	10'-4 3⁄4"	10'-2 7⁄16"	18'-10 1⁄8"	3'-9 1⁄8"			34'-10 1⁄8"	6'-5 1⁄8"				
10'-6"	10'-10 3⁄4"	10'-8 7⁄16"	19'-10 1⁄8"	3'-11 1⁄8"			32'-10 1⁄8"	6'-1 1⁄8"				
11'-0"	11'-4 3⁄4"	11'-2 7⁄16"	20'-10 1⁄8"	4'-1 1⁄8"			31'-4 1⁄8"	5'-10 1⁄8"				
11'-6"	11'-10 3⁄4"	11'-8 7⁄16"	21'-10 1⁄8"	4'-3 1⁄8"	29'-10 1⁄8"	5'-7 1⁄8"						
12'-0"	12'-4 3⁄4"	12'-2 7⁄16"	22'-10 1⁄8"	4'-5 1⁄8"	28'-10 1⁄8"	5'-5 1⁄8"						
> 12'-0"		Contact local Andersen supplier										

Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications.
Dimensions in parentheses are in millimeters.

Date: 7/11/18
Scale: None

Chart 5.0			Two-Directional - Two Panel									
Frame Depth = 3 ⁹ / ₁₆ " , Pocket Depth = 5 ⁵ / ₁₆ "												
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width							
			R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.		
			Rated			Not Rated						
			Without Intermediate Stile						With Intermediate Stile			
Contact local Andersen supplier												
< 6'-6"												
6'-6"	6'-10 ³ / ₄ "	6'-8 ⁷ / ₁₆ "	4'-7 ⁷ / ₁₆ "	2'-7 ¹ / ₈ "	14'-3 ⁷ / ₁₆ "	7'-5 ¹ / ₈ "	24'-3 ⁷ / ₁₆ "	12'-5 ¹ / ₈ "	Contact local Andersen supplier	Contact local Andersen supplier		
7'-0"	7'-4 ³ / ₄ "	7'-2 ⁷ / ₁₆ "	4'-11 ¹ / ₁₆ "	2'-9 ¹ / ₈ "								
7'-6"	7'-10 ³ / ₄ "	7'-8 ⁷ / ₁₆ "	5'-3 ⁷ / ₁₆ "	2'-11 ¹ / ₈ "								
8'-0"	8'-4 ³ / ₄ "	8'-2 ⁷ / ₁₆ "	5'-7 ⁷ / ₁₆ "	3'-1 ¹ / ₈ "								
8'-6"	8'-10 ³ / ₄ "	8'-8 ⁷ / ₁₆ "	5'-11 ⁷ / ₁₆ "	3'-3 ³ / ₈ "								
9'-0"	9'-4 ³ / ₄ "	9'-2 ⁷ / ₁₆ "	6'-3 ⁷ / ₁₆ "	3'-5 ¹ / ₈ "	13'-3 ⁷ / ₁₆ "	6'-11 ¹ / ₂ "	14'-3 ⁷ / ₁₆ "	7'-5 ¹ / ₈ "			Contact local Andersen supplier	Contact local Andersen supplier
9'-6"	9'-10 ³ / ₄ "	9'-8 ⁷ / ₁₆ "	6'-7 ⁷ / ₁₆ "	3'-7 ¹ / ₈ "	12'-7 ⁷ / ₁₆ "	6'-7 ¹ / ₈ "						
10'-0"	10'-4 ³ / ₄ "	10'-2 ⁷ / ₁₆ "	6'-11 ⁷ / ₁₆ "	3'-9 ¹ / ₈ "	12'-3 ⁷ / ₁₆ "	6'-5 ¹ / ₈ "						
10'-6"	10'-10 ³ / ₄ "	10'-8 ⁷ / ₁₆ "	7'-3 ⁷ / ₁₆ "	3'-11 ¹ / ₈ "	11'-7 ⁷ / ₁₆ "	6'-1 ¹ / ₈ "						
11'-0"	11'-4 ³ / ₄ "	11'-2 ⁷ / ₁₆ "	7'-7 ⁷ / ₁₆ "	4'-1 ¹ / ₈ "	11'-1 ⁷ / ₁₆ "	5'-10 ¹ / ₈ "						
11'-6"	11'-10 ³ / ₄ "	11'-8 ⁷ / ₁₆ "	7'-11 ⁷ / ₁₆ "	4'-3 ¹ / ₈ "	10'-7 ⁷ / ₁₆ "	5'-7 ¹ / ₈ "						
12'-0"	12'-4 ³ / ₄ "	12'-2 ⁷ / ₁₆ "	8'-3 ⁷ / ₁₆ "	4'-5 ¹ / ₈ "	10'-3 ⁷ / ₁₆ "	5'-5 ¹ / ₈ "						
> 12'-0"			Contact local Andersen supplier									






Chart 5.1		Two-Directional - Four Panel									
Head Jamb Depth at Astragal = 3 9/16", O.A. Frame Depth = 7 1/4", Pocket Depth = 9"											
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width						
			R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	
			Rated				Not Rated				
Without Intermediate Stile										With Intermediate Stile	
Contact local Andersen supplier											
< 6'-6"											
6'-6"	6'-10 3/4"	6'-8 7/16"	8'-4 7/16"	2'-7 1/8"	27'-8 7/16"	7'-5 1/8"	47'-6 7/16"	12'-5 1/8"	Contact local Andersen supplier	Contact local Andersen supplier	
7'-0"	7'-4 3/4"	7'-2 7/16"	9'-0 7/16"	2'-9 1/8"			27'-8 7/16"	7'-5 1/8"			
7'-6"	7'-10 3/4"	7'-8 7/16"	9'-8 7/16"	2'-11 1/8"							
8'-0"	8'-4 3/4"	8'-2 7/16"	10'-4 7/16"	3'-1 1/8"							
8'-6"	8'-10 3/4"	8'-8 7/16"	11'-0 7/16"	3'-3 3/8"							
9'-0"	9'-4 3/4"	9'-2 7/16"	11'-8 7/16"	3'-5 1/8"	25'-8 7/16"	6'-11 1/8"	27'-8 7/16"	7'-5 1/8"			
9'-6"	9'-10 3/4"	9'-8 7/16"	12'-4 7/16"	3'-7 3/8"	24'-4 7/16"	6'-7 3/8"					
10'-0"	10'-4 3/4"	10'-2 7/16"	13'-0 7/16"	3'-9 1/8"	23'-8 7/16"	6'-5 1/8"					
10'-6"	10'-10 3/4"	10'-8 7/16"	13'-8 7/16"	3'-11 1/8"	22'-4 7/16"	6'-1 1/8"					
11'-0"	11'-4 3/4"	11'-2 7/16"	14'-4 7/16"	4'-1 1/8"	21'-4 7/16"	5'-10 1/8"					
11'-6"	11'-10 3/4"	11'-8 7/16"	15'-0 7/16"	4'-3 3/8"	20'-4 7/16"	5'-7 1/8"					
12'-0"	12'-4 3/4"	12'-2 7/16"	15'-8 7/16"	4'-5 1/8"	19'-6 7/16"	5'-5 1/8"					
> 12'-0"					Contact local Andersen supplier						

Chart 5.2		Two-Directional - Six Panel										
Head Jamb Depth at Astragal = 3 ⁹ / ₁₆ " , O.A. Frame Depth = 10 ¹⁵ / ₁₆ " , Pocket Depth = 1'-0 ¹¹ / ₁₆ "												
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width							
			R.O.	Pocket R.O.	R.O.		Pocket R.O.		R.O.	Pocket R.O.	R.O.	Pocket R.O.
			Rated				Not Rated					
			Without Intermediate Stile							With Intermediate Stile		
Contact local Andersen supplier												
< 6'-6"												
6'-6"	6'-10 ³ / ₄ "	6'-8 ⁷ / ₁₆ "	12'-1 ⁷ / ₁₆ "	2'-7 ¹ / ₈ "	41'-1 ⁷ / ₁₆ "	7'-5 ¹ / ₈ "	71'-1 ⁷ / ₁₆ "	12'-5 ¹ / ₈ "	Contact local Andersen supplier	Contact local Andersen supplier		
7'-0"	7'-4 ³ / ₄ "	7'-2 ⁷ / ₁₆ "	13'-1 ⁷ / ₁₆ "	2'-9 ¹ / ₈ "			41'-1 ⁷ / ₁₆ "	7'-5 ¹ / ₈ "				
7'-6"	7'-10 ³ / ₄ "	7'-8 ⁷ / ₁₆ "	14'-1 ⁷ / ₁₆ "	2'-11 ¹ / ₈ "								
8'-0"	8'-4 ³ / ₄ "	8'-2 ⁷ / ₁₆ "	15'-1 ⁷ / ₁₆ "	3'-1 ¹ / ₈ "								
8'-6"	8'-10 ³ / ₄ "	8'-8 ⁷ / ₁₆ "	16'-1 ⁷ / ₁₆ "	3'-3 ³ / ₈ "								
9'-0"	9'-4 ³ / ₄ "	9'-2 ⁷ / ₁₆ "	17'-1 ⁷ / ₁₆ "	3'-5 ¹ / ₈ "	38'-1 ⁷ / ₁₆ "	6'-11 ¹ / ₈ "	41'-1 ⁷ / ₁₆ "	7'-5 ¹ / ₈ "				
9'-6"	9'-10 ³ / ₄ "	9'-8 ⁷ / ₁₆ "	18'-1 ⁷ / ₁₆ "	3'-7 ¹ / ₈ "	36'-1 ⁷ / ₁₆ "	6'-7 ¹ / ₈ "						
10'-0"	10'-4 ³ / ₄ "	10'-2 ⁷ / ₁₆ "	19'-1 ⁷ / ₁₆ "	3'-9 ¹ / ₈ "	35'-1 ⁷ / ₁₆ "	6'-5 ¹ / ₈ "						
10'-6"	10'-10 ³ / ₄ "	10'-8 ⁷ / ₁₆ "	20'-1 ⁷ / ₁₆ "	3'-11 ¹ / ₈ "	33'-1 ⁷ / ₁₆ "	6'-1 ¹ / ₈ "						
11'-0"	11'-4 ³ / ₄ "	11'-2 ⁷ / ₁₆ "	21'-1 ⁷ / ₁₆ "	4'-1 ¹ / ₈ "	31'-7 ⁷ / ₁₆ "	5'-10 ¹ / ₈ "						
11'-6"	11'-10 ³ / ₄ "	11'-8 ⁷ / ₁₆ "	22'-1 ⁷ / ₁₆ "	4'-3 ³ / ₈ "	30'-1 ⁷ / ₁₆ "	5'-7 ¹ / ₈ "						
12'-0"	12'-4 ³ / ₄ "	12'-2 ⁷ / ₁₆ "	23'-1 ⁷ / ₁₆ "	4'-5 ¹ / ₈ "	29'-1 ⁷ / ₁₆ "	5'-5 ¹ / ₈ "						
> 12'-0"					Contact local Andersen supplier							

Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications.
Dimensions in parentheses are in millimeters.

Date: 7/11/18
Scale: None




Chart 6.0		Two-Directional - Eight Panel									
Head Jamb Depth at Astragal = 3 9/16", O.A. Frame Depth = 1'-2 11/16", Pocket Depth = 1'-4 7/16"											
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width						
			R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	
			Rated				Not Rated				
			Without Intermediate Stile						With Intermediate Stile		
Contact local Andersen supplier											
< 6'-6"											
6'-6"	6'-10 3/4"	6'-8 7/16"	15'-10 7/16"	2'-7 1/8"	43'-9 3/4"	6'-1"	94'-6 7/16"	12'-5 1/8"	Contact local Andersen supplier	Contact local Andersen supplier	
7'-0"	7'-4 3/4"	7'-2 7/16"	17'-2 7/16"	2'-9 1/8"							
7'-6"	7'-10 3/4"	7'-8 7/16"	18'-6 7/16"	2'-11 1/8"							
8'-0"	8'-4 3/4"	8'-2 7/16"	19'-10 7/16"	3'-1 1/8"							
8'-6"	8'-10 3/4"	8'-8 7/16"	21'-2 7/16"	3'-3 1/8"							
9'-0"	9'-4 3/4"	9'-2 7/16"	22'-6 7/16"	3'-5 1/8"							
9'-6"	9'-10 3/4"	9'-8 7/16"	23'-10 7/16"	3'-7 1/8"							
10'-0"	10'-4 3/4"	10'-2 7/16"	25'-2 7/16"	3'-9 1/8"							
10'-6"	10'-10 3/4"	10'-8 7/16"	26'-6 7/16"	3'-11 1/8"							
11'-0"	11'-4 3/4"	11'-2 7/16"	27'-10 7/16"	4'-1 1/8"			41'-10 7/16"	5'-10 1/8"			
11'-6"	11'-10 3/4"	11'-8 7/16"	29'-2 7/16"	4'-3 1/8"	39'-10 7/16"	5'-7 1/8"					
12'-0"	12'-4 3/4"	12'-2 7/16"	30'-6 7/16"	4'-5 1/8"	38'-6 7/16"	5'-5 1/8"					
> 12'-0"			Contact local Andersen supplier								

Chart 6.1		Two-Directional - Ten Panel									
Head Jamb Depth at Astragal = 3 ⁹ / ₁₆ ", O.A. Frame Depth = 1'-6 ³ / ₈ ", Pocket Depth = 1'-8 ¹ / ₈ "											
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width						
			R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	
			Rated				Not Rated				
					Without Intermediate Stile					With Intermediate Stile	
Contact local Andersen supplier											
< 6'-6"											
6'-6"	6'-10 ³ / ₄ "	6'-8 ⁷ / ₁₆ "	19'-7 ⁷ / ₁₆ "	2'-7 ¹ / ₈ "	43'-9 ³ / ₄ "	5'-0 ¹ / ₈ "	117'-11 ⁷ / ₁₆ "	12'-5 ¹ / ₈ "	Contact local Andersen supplier	Contact local Andersen supplier	
7'-0"	7'-4 ³ / ₄ "	7'-2 ⁷ / ₁₆ "	21'-3 ⁷ / ₁₆ "	2'-9 ¹ / ₈ "							
7'-6"	7'-10 ³ / ₄ "	7'-8 ⁷ / ₁₆ "	22'-11 ⁷ / ₁₆ "	2'-11 ¹ / ₈ "							
8'-0"	8'-4 ³ / ₄ "	8'-2 ⁷ / ₁₆ "	24'-7 ⁷ / ₁₆ "	3'-1 ¹ / ₈ "							
8'-6"	8'-10 ³ / ₄ "	8'-8 ⁷ / ₁₆ "	26'-3 ⁷ / ₁₆ "	3'-3 ¹ / ₈ "							
9'-0"	9'-4 ³ / ₄ "	9'-2 ⁷ / ₁₆ "	27'-11 ⁷ / ₁₆ "	3'-5 ¹ / ₈ "							
9'-6"	9'-10 ³ / ₄ "	9'-8 ⁷ / ₁₆ "	29'-7 ⁷ / ₁₆ "	3'-7 ¹ / ₈ "							
10'-0"	10'-4 ³ / ₄ "	10'-2 ⁷ / ₁₆ "	31'-3 ⁷ / ₁₆ "	3'-9 ¹ / ₈ "							
10'-6"	10'-10 ³ / ₄ "	10'-8 ⁷ / ₁₆ "	32'-11 ⁷ / ₁₆ "	3'-11 ¹ / ₈ "							
11'-0"	11'-4 ³ / ₄ "	11'-2 ⁷ / ₁₆ "	34'-7 ⁷ / ₁₆ "	4'-1 ¹ / ₈ "							
11'-6"	11'-10 ³ / ₄ "	11'-8 ⁷ / ₁₆ "	36'-3 ⁷ / ₁₆ "	4'-3 ¹ / ₈ "							
12'-0"	12'-4 ³ / ₄ "	12'-2 ⁷ / ₁₆ "	37'-11 ⁷ / ₁₆ "	4'-5 ¹ / ₈ "							
> 12'-0"					Contact local Andersen supplier						

Chart 6.2		Two-Directional - Twelve Panel									
Head Jamb Depth at Astragal = 3 9/16", O.A. Frame Depth = 1'-10 1/16", Pocket Depth = 1'-11 13/16"											
Panel Height	R.O. Height	Top of F.F. to Bottom of Header	Minimum Width		Maximum Width						
			R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	R.O.	Pocket R.O.	
			Rated				Not Rated				
			Without Intermediate Stile						With Intermediate Stile		
< 6'-6"		Contact local Andersen supplier									
6'-6"	6'-10 3/4"	6'-8 7/16"	23'-4 7/16"	2'-7 7/8"	43'-9 3/4"	4'-3 9/16"	141'-4 7/16"	12'-5 1/8"	Contact local Andersen supplier	Contact local Andersen supplier	
7'-0"	7'-4 3/4"	7'-2 7/16"	25'-4 7/16"	2'-9 1/8"			81'-4 7/16"	7'-5 1/8"			
7'-6"	7'-10 3/4"	7'-8 7/16"	27'-4 7/16"	2'-11 1/8"							
8'-0"	8'-4 3/4"	8'-2 7/16"	29'-4 7/16"	3'-1 1/8"							
8'-6"	8'-10 3/4"	8'-8 7/16"	31'-4 7/16"	3'-3 7/8"							
9'-0"	9'-4 3/4"	9'-2 7/16"	33'-4 7/16"	3'-5 1/8"							
9'-6"	9'-10 3/4"	9'-8 7/16"	35'-4 7/16"	3'-7 7/8"							
10'-0"	10'-4 3/4"	10'-2 7/16"	37'-4 7/16"	3'-9 1/8"							
10'-6"	10'-10 3/4"	10'-8 7/16"	39'-4 7/16"	3'-11 1/8"							
11'-0"	11'-4 3/4"	11'-2 7/16"	41'-4 7/16"	4'-1 1/8"							
11'-6"	11'-10 3/4"	11'-8 7/16"	43'-4 7/16"	4'-3 1/8"							
12'-0"	12'-4 3/4"	12'-2 7/16"	45'-4 7/16"	4'-5 1/8"							
> 12'-0"		Contact local Andersen supplier									

Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications.
Dimensions in parentheses are in millimeters.

Date: 7/11/18
Scale: None