







# Big Doors

Weiland™ Pocket Liftslide  
Aluminum Wood - With Screens



Additional Configurations - More configurations available.  
Contact your local Andersen supplier for additional information.



## Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications.  
Dimensions in parentheses are in millimeters.

See Page 22 for Glazing Accessories


Date: 7/11/18  
Scale: None

# Big Doors

Weiland™ Pocket Liftslide  
Aluminum Wood - With Screens



Additional Configurations - More configurations available.  
Contact your local Andersen supplier for additional information.



## Notes:




Details have been optimized for use in architectural software and do not match manufacturing specifications.  
Dimensions in parentheses are in millimeters.

See Page 22 for Glazing Accessories

Date: 7/11/18  
Scale: None


# Big Doors

Weiland™ Pocket Liftslide  
Aluminum Wood - With Screens



**IMPORTANT**

For more detailed information pertaining to product application. See the Weiland® Liftslide Site Prep Guide.



## Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications. Dimensions in parentheses are in millimeters.


See Page 22 for Glazing Accessories

Date: 7/11/18  
Scale: 3/8" (10) = 1' (305)

# Big Doors

Weiland™ Pocket Liftslide  
Aluminum Wood - With Screens

**Andersen®**  
ARCHITECTURAL  
COLLECTION



## Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications.  
Dimensions in parentheses are in millimeters.

See Page 22 for Glazing Accessories

Date: 7/11/18  
Scale: 3/8" (10) = 1' (305)

# Big Doors

Weiland™ Pocket Liftslide  
Aluminum Wood - With Screens

## Line Types


- Perimeter of head jamb
- Sill tracks
- Panel and jamb outline
- Rough opening

## IMPORTANT




For more detailed information pertaining to product application. See the **Weiland® Liftslide Site Prep Guide.**

## Head Track Options

### Staggered Track (Standard)



### Full Track



## Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications. Dimensions in parentheses are in millimeters.


**See Page 22 for Glazing Accessories**

Date: 7/11/18  
Scale: 3/8" (10) = 1' (305)

# Big Doors

Weiland™ Pocket Liftslide  
Aluminum Wood - With Screens

**Andersen**®  
ARCHITECTURAL  
COLLECTION






## Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications.  
Dimensions in parentheses are in millimeters.

See Page 22 for Glazing Accessories

Date: 7/11/18  
Scale: 3/8" (10) = 1' (305)

| Chart 7.0                                   |             | One-Directional - One Panel     |               |             |                                 |             |            |                         |                                 |                                 |  |  |
|---|-------------|---------------------------------|---------------|-------------|---------------------------------|-------------|------------|-------------------------|---------------------------------|---------------------------------|--|--|
| Lock Jamb Depth = 6 1/4", Pocket Depth = 8" |             |                                 |               |             |                                 |             |            |                         |                                 |                                 |  |  |
| Panel Height                                | R.O. Height | Top of F.F. to Bottom of Header | Minimum Width |             | Maximum Width                   |             |            |                         |                                 |                                 |  |  |
|   |             |                                 | R.O.          | Pocket R.O. | R.O.                            | Pocket R.O. | R.O.       | Pocket R.O.             | R.O.                            | Pocket R.O.                     |  |  |
|   |             |                                 | Rated         |             |                                 |             | Not Rated  |                         |                                 |                                 |  |  |
| Without Intermediate Stile                  |             |                                 |               |             |                                 |             |            | With Intermediate Stile |                                 |                                 |  |  |
| Contact local Andersen supplier             |             |                                 |               |             |                                 |             |            |                         |                                 |                                 |  |  |
| < 6'-6"                                     |             |                                 |               |             |                                 |             |            |                         |                                 |                                 |  |  |
| 6'-6"                                       | 6'-10 3/4"  | 6'-8 7/16"                      | 2'-5 5/8"     | 2'-7 1/8"   | 7'-3 5/8"                       | 7'-5 1/8"   | 12'-3 5/8" | 12'-5 1/8"              | Contact local Andersen supplier | Contact local Andersen supplier |  |  |
| 7'-0"                                       | 7'-4 3/4"   | 7'-2 7/16"                      | 2'-7 5/8"     | 2'-9 1/8"   |                                 |             |            |                         |                                 |                                 |  |  |
| 7'-6"                                       | 7'-10 3/4"  | 7'-8 7/16"                      | 2'-9 5/8"     | 2'-11 1/8"  |                                 |             |            |                         |                                 |                                 |  |  |
| 8'-0"                                       | 8'-4 3/4"   | 8'-2 7/16"                      | 2'-11 5/8"    | 3'-1 1/8"   |                                 |             |            |                         |                                 |                                 |  |  |
| 8'-6"                                       | 8'-10 3/4"  | 8'-8 7/16"                      | 3'-1 5/8"     | 3'-3 1/8"   |                                 |             |            |                         |                                 |                                 |  |  |
| 9'-0"                                       | 9'-4 3/4"   | 9'-2 7/16"                      | 3'-3 5/8"     | 3'-5 1/8"   | 6'-9 5/8"                       | 6'-11 1/8"  | 7'-3 5/8"  | 7'-5 1/8"               |                                 |                                 |  |  |
| 9'-6"                                       | 9'-10 3/4"  | 9'-8 7/16"                      | 3'-5 5/8"     | 3'-7 1/8"   | 6'-5 5/8"                       | 6'-7 1/8"   |            |                         |                                 |                                 |  |  |
| 10'-0"                                      | 10'-4 3/4"  | 10'-2 7/16"                     | 3'-7 5/8"     | 3'-9 1/8"   | 6'-3 5/8"                       | 6'-5 1/8"   |            |                         |                                 |                                 |  |  |
| 10'-6"                                      | 10'-10 3/4" | 10'-8 7/16"                     | 3'-9 5/8"     | 3'-11 1/8"  | 5'-11 5/8"                      | 6'-1 1/8"   |            |                         |                                 |                                 |  |  |
| 11'-0"                                      | 11'-4 3/4"  | 11'-2 7/16"                     | 3'-11 5/8"    | 4'-1 1/8"   | 5'-8 5/8"                       | 5'-10 1/8"  |            |                         |                                 |                                 |  |  |
| 11'-6"                                      | 11'-10 3/4" | 11'-8 7/16"                     | 4'-1 5/8"     | 4'-3 1/8"   | 5'-5 5/8"                       | 5'-7 1/8"   | 7'-3 5/8"  | 7'-5 1/8"               |                                 |                                 |  |  |
| 12'-0"                                      | 12'-4 3/4"  | 12'-2 7/16"                     | 4'-3 5/8"     | 4'-5 1/8"   | 5'-3 5/8"                       | 5'-5 1/8"   |            |                         |                                 |                                 |  |  |
| > 12'-0"                                    |             |                                 |               |             | Contact local Andersen supplier |             |            |                         |                                 |                                 |  |  |



| Chart 7.1  |             | One-Directional - Two Panel     |                            |             |               |             |            |             |                                 |                                 |  |  |  |
|--|-------------|---------------------------------|----------------------------|-------------|---------------|-------------|------------|-------------|---------------------------------|---------------------------------|--|--|--|
| Lock Jamb Depth = 8 1/16", O.A. Frame Depth = 11 3/4", Pocket Depth = 1'-1 9/16" |             |                                 |                            |             |               |             |            |             |                                 |                                 |  |  |  |
| Panel Height   | R.O. Height | Top of F.F. to Bottom of Header | Minimum Width              |             | Maximum Width |             |            |             |                                 |                                 |  |  |  |
|  |             |                                 | R.O.                       | Pocket R.O. | R.O.          | Pocket R.O. | R.O.       | Pocket R.O. | R.O.                            | Pocket R.O.                     |  |  |  |
|  |             |                                 | Rated                      |             |               |             | Not Rated  |             |                                 |                                 |  |  |  |
|  |             |                                 | Without Intermediate Stile |             |               |             |            |             | With Intermediate Stile         |                                 |  |  |  |
| < 6'-6"  |             | Contact local Andersen supplier |                            |             |               |             |            |             |                                 |                                 |  |  |  |
| 6'-6"  | 6'-10 3/4"  | 6'-8 7/16"                      | 4'-4 1/8"                  | 2'-7 1/8"   | 14'-0 1/8"    | 7'-5 1/8"   | 24'-0 1/8" | 12'-5 1/8"  | Contact local Andersen supplier | Contact local Andersen supplier |  |  |  |
| 7'-0"  | 7'-4 3/4"   | 7'-2 7/16"                      | 4'-8 1/8"                  | 2'-9 1/8"   |               |             | 14'-0 1/8" | 7'-5 1/8"   |                                 |                                 |  |  |  |
| 7'-6"  | 7'-10 3/4"  | 7'-8 7/16"                      | 5'-0 1/8"                  | 2'-11 1/8"  |               |             |            |             |                                 |                                 |  |  |  |
| 8'-0"  | 8'-4 3/4"   | 8'-2 7/16"                      | 5'-4 1/8"                  | 3'-1 1/8"   |               |             |            |             |                                 |                                 |  |  |  |
| 8'-6"  | 8'-10 3/4"  | 8'-8 7/16"                      | 5'-8 1/8"                  | 3'-3 1/8"   |               |             |            |             |                                 |                                 |  |  |  |
| 9'-0"  | 9'-4 3/4"   | 9'-2 7/16"                      | 6'-0 1/8"                  | 3'-5 1/8"   | 13'-0 1/8"    | 6'-11 1/8"  | 14'-0 1/8" | 7'-5 1/8"   |                                 |                                 |  |  |  |
| 9'-6"  | 9'-10 3/4"  | 9'-8 7/16"                      | 6'-4 1/8"                  | 3'-7 1/8"   | 12'-4 1/8"    | 6'-7 1/8"   |            |             |                                 |                                 |  |  |  |
| 10'-0"   | 10'-4 3/4"  | 10'-2 7/16"                     | 6'-8 1/8"                  | 3'-9 1/8"   | 12'-0 1/8"    | 6'-5 1/8"   |            |             |                                 |                                 |  |  |  |
| 10'-6"   | 10'-10 3/4" | 10'-8 7/16"                     | 7'-0 1/8"                  | 3'-11 1/8"  | 11'-4 1/8"    | 6'-1 1/8"   |            |             |                                 |                                 |  |  |  |
| 11'-0"   | 11'-4 3/4"  | 11'-2 7/16"                     | 7'-4 1/8"                  | 4'-1 1/8"   | 10'-10 1/8"   | 5'-10 1/8"  |            |             |                                 |                                 |  |  |  |
| 11'-6"   | 11'-10 3/4" | 11'-8 7/16"                     | 7'-8 1/8"                  | 4'-3 1/8"   | 10'-4 1/8"    | 5'-7 1/8"   | 14'-0 1/8" | 7'-5 1/8"   |                                 |                                 |  |  |  |
| 12'-0"   | 12'-4 3/4"  | 12'-2 7/16"                     | 8'-0 1/8"                  | 4'-5 1/8"   | 10'-0 1/8"    | 5'-5 1/8"   |            |             |                                 |                                 |  |  |  |
| > 12'-0"   |             | Contact local Andersen supplier |                            |             |               |             |            |             |                                 |                                 |  |  |  |

| Chart 7.2  |             | One-Directional - Three Panel   |                                 |             |               |             |            |             |                                 |                                 |  |  |  |
|--|-------------|---------------------------------|---------------------------------|-------------|---------------|-------------|------------|-------------|---------------------------------|---------------------------------|--|--|--|
| Lock Jamb Depth = 9 7⁄8", O.A. Frame Depth = 1'-5 5⁄16", Pocket Depth = 1'-7 1⁄16" |             |                                 |                                 |             |               |             |            |             |                                 |                                 |  |  |  |
| Panel Height   | R.O. Height | Top of F.F. to Bottom of Header | Minimum Width                   |             | Maximum Width |             |            |             |                                 |                                 |  |  |  |
|  |             |                                 | R.O.                            | Pocket R.O. | R.O.          | Pocket R.O. | R.O.       | Pocket R.O. | R.O.                            | Pocket R.O.                     |  |  |  |
|  |             |                                 | Rated                           |             |               |             | Not Rated  |             |                                 |                                 |  |  |  |
|  |             |                                 | Without Intermediate Stile      |             |               |             |            |             | With Intermediate Stile         |                                 |  |  |  |
| Contact local Andersen supplier  |             |                                 |                                 |             |               |             |            |             |                                 |                                 |  |  |  |
| < 6'-6"  |             |                                 |                                 |             |               |             |            |             |                                 |                                 |  |  |  |
| 6'-6"  | 6'-10 3⁄4"  | 6'-8 7⁄16"                      | 6'-2 5⁄8"                       | 2'-7 1⁄8"   | 20'-8 5⁄8"    | 7'-5 1⁄8"   | 35'-8 5⁄8" | 12'-5 1⁄8"  | Contact local Andersen supplier | Contact local Andersen supplier |  |  |  |
| 7'-0"  | 7'-4 3⁄4"   | 7'-2 7⁄16"                      | 6'-8 5⁄8"                       | 2'-9 1⁄8"   |               |             |            |             |                                 |                                 |  |  |  |
| 7'-6"  | 7'-10 3⁄4"  | 7'-8 7⁄16"                      | 7'-2 5⁄8"                       | 2'-11 1⁄8"  |               |             |            |             |                                 |                                 |  |  |  |
| 8'-0"  | 8'-4 3⁄4"   | 8'-2 7⁄16"                      | 7'-8 5⁄8"                       | 3'-1 1⁄8"   |               |             |            |             |                                 |                                 |  |  |  |
| 8'-6"  | 8'-10 3⁄4"  | 8'-8 7⁄16"                      | 8'-2 5⁄8"                       | 3'-3 1⁄8"   |               |             |            |             |                                 |                                 |  |  |  |
| 9'-0"  | 9'-4 3⁄4"   | 9'-2 7⁄16"                      | 8'-8 5⁄8"                       | 3'-5 1⁄8"   | 19'-2 5⁄8"    | 6'-11 1⁄8"  | 20'-8 5⁄8" | 7'-5 1⁄8"   |                                 |                                 |  |  |  |
| 9'-6"  | 9'-10 3⁄4"  | 9'-8 7⁄16"                      | 9'-2 5⁄8"                       | 3'-7 1⁄8"   | 18'-2 5⁄8"    | 6'-7 1⁄8"   |            |             |                                 |                                 |  |  |  |
| 10'-0"   | 10'-4 3⁄4"  | 10'-2 7⁄16"                     | 9'-8 5⁄8"                       | 3'-9 1⁄8"   | 17'-8 5⁄8"    | 6'-5 1⁄8"   |            |             |                                 |                                 |  |  |  |
| 10'-6"   | 10'-10 3⁄4" | 10'-8 7⁄16"                     | 10'-2 5⁄8"                      | 3'-11 1⁄8"  | 16'-8 5⁄8"    | 6'-1 1⁄8"   |            |             |                                 |                                 |  |  |  |
| 11'-0"   | 11'-4 3⁄4"  | 11'-2 7⁄16"                     | 10'-8 5⁄8"                      | 4'-1 1⁄8"   | 15'-11 5⁄8"   | 5'-10 1⁄8"  |            |             |                                 |                                 |  |  |  |
| 11'-6"   | 11'-10 3⁄4" | 11'-8 7⁄16"                     | 11'-2 5⁄8"                      | 4'-3 1⁄8"   | 15'-2 5⁄8"    | 5'-7 1⁄8"   |            |             |                                 |                                 |  |  |  |
| 12'-0"   | 12'-4 3⁄4"  | 12'-2 7⁄16"                     | 11'-8 5⁄8"                      | 4'-5 1⁄8"   | 14'-8 5⁄8"    | 5'-5 1⁄8"   |            |             |                                 |                                 |  |  |  |
| > 12'-0"   |             |                                 | Contact local Andersen supplier |             |               |             |            |             |                                 |                                 |  |  |  |




## Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications.  
Dimensions in parentheses are in millimeters.

See Page 22 for Glazing Accessories

Date: 7/11/18  
Scale: None

| Chart 8.0   |             | One-Directional - Four Panel    |                                 |             |               |             |            |             |                                 |                                 |  |
|---|-------------|---------------------------------|---------------------------------|-------------|---------------|-------------|------------|-------------|---------------------------------|---------------------------------|--|
| Lock Jamb Depth = 11 11⁄16", O.A. Frame Depth = 1'-10 13⁄16", Pocket Depth = 2'-0 9⁄16" |             |                                 |                                 |             |               |             |            |             |                                 |                                 |  |
| Panel Height  | R.O. Height | Top of F.F. to Bottom of Header | Minimum Width                   |             | Maximum Width |             |            |             |                                 |                                 |  |
|   |             |                                 | R.O.                            | Pocket R.O. | R.O.          | Pocket R.O. | R.O.       | Pocket R.O. | R.O.                            | Pocket R.O.                     |  |
|   |             |                                 | Rated                           |             |               | Not Rated   |            |             |                                 |                                 |  |
|   |             |                                 | Without Intermediate Stile      |             |               |             |            |             | With Intermediate Stile         |                                 |  |
| < 6'-6"   |             |                                 | Contact local Andersen supplier |             |               |             |            |             |                                 |                                 |  |
| 6'-6"   | 6'-10 3⁄4"  | 6'-8 7⁄16"                      | 8'-1 1⁄8"                       | 2'-7 1⁄8"   | 27'-5 1⁄8"    | 7'-5 1⁄8"   | 47'-3 1⁄8" | 12'-5 1⁄8"  | Contact local Andersen supplier | Contact local Andersen supplier |  |
| 7'-0"   | 7'-4 3⁄4"   | 7'-2 7⁄16"                      | 8'-9 1⁄8"                       | 2'-9 1⁄8"   |               |             | 27'-5 1⁄8" | 7'-5 1⁄8"   |                                 |                                 |  |
| 7'-6"   | 7'-10 3⁄4"  | 7'-8 7⁄16"                      | 9'-5 1⁄8"                       | 2'-11 1⁄8"  |               |             |            |             |                                 |                                 |  |
| 8'-0"   | 8'-4 3⁄4"   | 8'-2 7⁄16"                      | 10'-1 1⁄8"                      | 3'-1 1⁄8"   |               |             |            |             |                                 |                                 |  |
| 8'-6"   | 8'-10 3⁄4"  | 8'-8 7⁄16"                      | 10'-9 1⁄8"                      | 3'-3 1⁄8"   |               |             |            |             |                                 |                                 |  |
| 9'-0"   | 9'-4 3⁄4"   | 9'-2 7⁄16"                      | 11'-5 1⁄8"                      | 3'-5 1⁄8"   | 25'-5 1⁄8"    | 6'-11 1⁄8"  |            |             |                                 |                                 |  |
| 9'-6"   | 9'-10 3⁄4"  | 9'-8 7⁄16"                      | 12'-1 1⁄8"                      | 3'-7 1⁄8"   | 24'-1 1⁄8"    | 6'-7 1⁄8"   |            |             |                                 |                                 |  |
| 10'-0"  | 10'-4 3⁄4"  | 10'-2 7⁄16"                     | 12'-9 1⁄8"                      | 3'-9 1⁄8"   | 23'-5 1⁄8"    | 6'-5 1⁄8"   |            |             |                                 |                                 |  |
| 10'-6"  | 10'-10 3⁄4" | 10'-8 7⁄16"                     | 13'-5 1⁄8"                      | 3'-11 1⁄8"  | 22'-1 1⁄8"    | 6'-1 1⁄8"   |            |             |                                 |                                 |  |
| 11'-0"  | 11'-4 3⁄4"  | 11'-2 7⁄16"                     | 14'-1 1⁄8"                      | 4'-1 1⁄8"   | 21'-1 1⁄8"    | 5'-10 1⁄8"  |            |             |                                 |                                 |  |
| 11'-6"  | 11'-10 3⁄4" | 11'-8 7⁄16"                     | 14'-9 1⁄8"                      | 4'-3 1⁄8"   | 20'-1 1⁄8"    | 5'-7 1⁄8"   |            |             |                                 |                                 |  |
| 12'-0"  | 12'-4 3⁄4"  | 12'-2 7⁄16"                     | 15'-5 1⁄8"                      | 4'-5 1⁄8"   | 19'-3 1⁄8"    | 5'-5 1⁄8"   |            |             |                                 |                                 |  |
| > 12'-0"  |             |                                 | Contact local Andersen supplier |             |               |             |            |             |                                 |                                 |  |



| Chart 8.1  |                                 |                                 | One-Directional - Five Panel |             |               |            |             |            |                                 |                                 |  |  |  |  |  |
|--|---------------------------------|---------------------------------|------------------------------|-------------|---------------|------------|-------------|------------|---------------------------------|---------------------------------|--|--|--|--|--|
| Lock Jamb Depth = 1'-1 9/16", O.A. Frame Depth = 2'-4 3/8", Pocket Depth = 2'-6 1/8" |                                 |                                 |                              |             |               |            |             |            |                                 |                                 |  |  |  |  |  |
| Panel Height   | R.O. Height                     | Top of F.F. to Bottom of Header | Minimum Width                |             | Maximum Width |            |             |            |                                 |                                 |  |  |  |  |  |
|  |                                 |                                 | R.O.                         | Pocket R.O. | R.O.          |            | Pocket R.O. |            | R.O.                            | Pocket R.O.                     |  |  |  |  |  |
|  |                                 |                                 | Rated                        |             |               |            | Not Rated   |            |                                 |                                 |  |  |  |  |  |
|  |                                 |                                 | Without Intermediate Stile   |             |               |            |             |            | With Intermediate Stile         |                                 |  |  |  |  |  |
| Contact local Andersen supplier  |                                 |                                 |                              |             |               |            |             |            |                                 |                                 |  |  |  |  |  |
| 6'-6"  | 6'-10 3/4"                      | 6'-8 7/16"                      | 9'-11 5/8"                   | 2'-7 1/8"   | 34'-1 5/8"    | 7'-5 1/8"  | 59'-1 5/8"  | 12'-5 1/8" | Contact local Andersen supplier | Contact local Andersen supplier |  |  |  |  |  |
| 7'-0"  | 7'-4 3/4"                       | 7'-2 7/16"                      | 10'-9 5/8"                   | 2'-9 1/8"   |               |            | 34'-1 5/8"  | 7'-5 1/8"  |                                 |                                 |  |  |  |  |  |
| 7'-6"  | 7'-10 3/4"                      | 7'-8 7/16"                      | 11'-7 5/8"                   | 2'-11 1/8"  |               |            |             |            |                                 |                                 |  |  |  |  |  |
| 8'-0"  | 8'-4 3/4"                       | 8'-2 7/16"                      | 12'-5 5/8"                   | 3'-1 1/8"   |               |            |             |            |                                 |                                 |  |  |  |  |  |
| 8'-6"  | 8'-10 3/4"                      | 8'-8 7/16"                      | 13'-3 5/8"                   | 3'-3 1/8"   |               |            |             |            |                                 |                                 |  |  |  |  |  |
| 9'-0"  | 9'-4 3/4"                       | 9'-2 7/16"                      | 14'-1 5/8"                   | 3'-5 1/8"   |               |            |             |            |                                 |                                 |  |  |  |  |  |
| 9'-6"  | 9'-10 3/4"                      | 9'-8 7/16"                      | 14'-11 5/8"                  | 3'-7 1/8"   | 29'-11 5/8"   | 6'-7 7/8"  |             |            |                                 |                                 |  |  |  |  |  |
| 10'-0"   | 10'-4 3/4"                      | 10'-2 7/16"                     | 15'-9 5/8"                   | 3'-9 1/8"   | 29'-1 5/8"    | 6'-5 1/8"  |             |            |                                 |                                 |  |  |  |  |  |
| 10'-6"   | 10'-10 3/4"                     | 10'-8 7/16"                     | 16'-7 5/8"                   | 3'-11 1/8"  | 27'-5 5/8"    | 6'-1 1/8"  |             |            |                                 |                                 |  |  |  |  |  |
| 11'-0"   | 11'-4 3/4"                      | 11'-2 7/16"                     | 17'-5 5/8"                   | 4'-1 1/8"   | 26'-2 5/8"    | 5'-10 1/8" |             |            |                                 |                                 |  |  |  |  |  |
| 11'-6"   | 11'-10 3/4"                     | 11'-8 7/16"                     | 18'-3 5/8"                   | 4'-3 1/8"   | 24'-11 5/8"   | 5'-7 1/8"  |             |            |                                 |                                 |  |  |  |  |  |
| 12'-0"   | 12'-4 3/4"                      | 12'-2 7/16"                     | 19'-1 5/8"                   | 4'-5 1/8"   | 24'-1 5/8"    | 5'-5 1/8"  |             |            |                                 |                                 |  |  |  |  |  |
| > 12'-0"   | Contact local Andersen supplier |                                 |                              |             |               |            |             |            |                                 |                                 |  |  |  |  |  |

| Chart 8.2  |             | One-Directional - Six Panel     |                            |             |               |             |             |             |                                 |                                 |  |
|--|-------------|---------------------------------|----------------------------|-------------|---------------|-------------|-------------|-------------|---------------------------------|---------------------------------|--|
| Lock Jamb Depth = 1'-3 3⁄8", O.A. Frame Depth = 2'-9 7⁄8", Pocket Depth = 2'-11 5⁄8" |             |                                 |                            |             |               |             |             |             |                                 |                                 |  |
| Panel Height   | R.O. Height | Top of F.F. to Bottom of Header | Minimum Width              |             | Maximum Width |             |             |             |                                 |                                 |  |
|  |             |                                 | R.O.                       | Pocket R.O. | R.O.          | Pocket R.O. | R.O.        | Pocket R.O. | R.O.                            | Pocket R.O.                     |  |
|  |             |                                 | Rated                      |             |               | Not Rated   |             |             |                                 |                                 |  |
|  |             |                                 | Without Intermediate Stile |             |               |             |             |             | With Intermediate Stile         |                                 |  |
| < 6'-6"  |             | Contact local Andersen supplier |                            |             |               |             |             |             |                                 |                                 |  |
| 6'-6"  | 6'-10 3⁄4"  | 6'-8 7⁄16"                      | 11'-10 1⁄8"                | 2'-7 1⁄8"   | 40'-10 1⁄8"   | 7'-5 1⁄8"   | 70'-10 1⁄8" | 12'-5 1⁄8"  | Contact local Andersen supplier | Contact local Andersen supplier |  |
| 7'-0"  | 7'-4 3⁄4"   | 7'-2 7⁄16"                      | 12'-10 1⁄8"                | 2'-9 1⁄8"   |               |             | 40'-10 1⁄8" | 7'-5 1⁄8"   |                                 |                                 |  |
| 7'-6"  | 7'-10 3⁄4"  | 7'-8 7⁄16"                      | 13'-10 1⁄8"                | 2'-11 1⁄8"  |               |             |             |             |                                 |                                 |  |
| 8'-0"  | 8'-4 3⁄4"   | 8'-2 7⁄16"                      | 14'-10 1⁄8"                | 3'-1 1⁄8"   |               |             |             |             |                                 |                                 |  |
| 8'-6"  | 8'-10 3⁄4"  | 8'-8 7⁄16"                      | 15'-10 1⁄8"                | 3'-3 1⁄8"   |               |             |             |             |                                 |                                 |  |
| 9'-0"  | 9'-4 3⁄4"   | 9'-2 7⁄16"                      | 16'-10 1⁄8"                | 3'-5 1⁄8"   | 37'-10 1⁄8"   | 6'-11 1⁄8"  |             |             |                                 |                                 |  |
| 9'-6"  | 9'-10 3⁄4"  | 9'-8 7⁄16"                      | 17'-10 1⁄8"                | 3'-7 1⁄8"   | 35'-10 1⁄8"   | 6'-7 1⁄8"   |             |             |                                 |                                 |  |
| 10'-0"   | 10'-4 3⁄4"  | 10'-2 7⁄16"                     | 18'-10 1⁄8"                | 3'-9 1⁄8"   | 34'-10 1⁄8"   | 6'-5 1⁄8"   |             |             |                                 |                                 |  |
| 10'-6"   | 10'-10 3⁄4" | 10'-8 7⁄16"                     | 19'-10 1⁄8"                | 3'-11 1⁄8"  | 32'-10 1⁄8"   | 6'-1 1⁄8"   |             |             |                                 |                                 |  |
| 11'-0"   | 11'-4 3⁄4"  | 11'-2 7⁄16"                     | 20'-10 1⁄8"                | 4'-1 1⁄8"   | 31'-4 1⁄8"    | 5'-10 1⁄8"  |             |             |                                 |                                 |  |
| 11'-6"   | 11'-10 3⁄4" | 11'-8 7⁄16"                     | 21'-10 1⁄8"                | 4'-3 1⁄8"   | 29'-10 1⁄8"   | 5'-7 1⁄8"   |             |             |                                 |                                 |  |
| 12'-0"   | 12'-4 3⁄4"  | 12'-2 7⁄16"                     | 22'-10 1⁄8"                | 4'-5 1⁄8"   | 28'-10 1⁄8"   | 5'-5 1⁄8"   |             |             |                                 |                                 |  |
| > 12'-0"   |             | Contact local Andersen supplier |                            |             |               |             |             |             |                                 |                                 |  |


## Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications.  
Dimensions in parentheses are in millimeters.

See Page 22 for Glazing Accessories

Date: 7/11/18  
Scale: None





| Chart 9.0                               |             |                                 | Two-Directional - Two Panel     |             |               |             |             |             |                                 |                                 |
|---|-------------|---------------------------------|---------------------------------|-------------|---------------|-------------|-------------|-------------|---------------------------------|---------------------------------|
| Frame Depth = 6 1/4", Pocket Depth = 8" |             |                                 |                                 |             |               |             |             |             |                                 |                                 |
| Panel Height                            | R.O. Height | Top of F.F. to Bottom of Header | Minimum Width                   |             | Maximum Width |             |             |             |                                 |                                 |
|   |             |                                 | R.O.                            | Pocket R.O. | R.O.          | Pocket R.O. | R.O.        | Pocket R.O. | R.O.                            | Pocket R.O.                     |
|   |             |                                 | Rated                           |             |               | Not Rated   |             |             |                                 |                                 |
|   |             |                                 | Without Intermediate Stile      |             |               |             |             |             | With Intermediate Stile         |                                 |
| < 6'-6"                                 |             |                                 | Contact local Andersen supplier |             |               |             |             |             |                                 |                                 |
| 6'-6"                                   | 6'-10 3/4"  | 6'-8 7/16"                      | 4'-7 7/16"                      | 2'-7 1/8"   | 14'-3 7/16"   | 7'-5 1/8"   | 24'-3 7/16" | 12'-5 1/8"  | Contact local Andersen supplier | Contact local Andersen supplier |
| 7'-0"                                   | 7'-4 3/4"   | 7'-2 7/16"                      | 4'-11 7/16"                     | 2'-9 1/8"   |               |             |             |             |                                 |                                 |
| 7'-6"                                   | 7'-10 3/4"  | 7'-8 7/16"                      | 5'-3 1/16"                      | 2'-11 1/8"  |               |             |             |             |                                 |                                 |
| 8'-0"                                   | 8'-4 3/4"   | 8'-2 7/16"                      | 5'-7 7/16"                      | 3'-1 1/8"   |               |             |             |             |                                 |                                 |
| 8'-6"                                   | 8'-10 3/4"  | 8'-8 7/16"                      | 5'-11 7/16"                     | 3'-3 3/8"   |               |             |             |             |                                 |                                 |
| 9'-0"                                   | 9'-4 3/4"   | 9'-2 7/16"                      | 6'-3 7/16"                      | 3'-5 1/8"   | 13'-3 7/16"   | 6'-11 1/2"  |             |             |                                 |                                 |
| 9'-6"                                   | 9'-10 3/4"  | 9'-8 7/16"                      | 6'-7 7/16"                      | 3'-7 1/8"   | 12'-7 7/16"   | 6'-7 1/8"   |             |             |                                 |                                 |
| 10'-0"                                  | 10'-4 3/4"  | 10'-2 7/16"                     | 6'-11 7/16"                     | 3'-9 1/8"   | 12'-3 7/16"   | 6'-5 1/8"   |             |             |                                 |                                 |
| 10'-6"                                  | 10'-10 3/4" | 10'-8 7/16"                     | 7'-3 7/16"                      | 3'-11 1/8"  | 11'-7 7/16"   | 6'-1 1/8"   |             |             |                                 |                                 |
| 11'-0"                                  | 11'-4 3/4"  | 11'-2 7/16"                     | 7'-7 7/16"                      | 4'-1 1/8"   | 11'-1 7/16"   | 5'-10 1/8"  |             |             |                                 |                                 |
| 11'-6"                                  | 11'-10 3/4" | 11'-8 7/16"                     | 7'-11 7/16"                     | 4'-3 3/8"   | 10'-7 7/16"   | 5'-7 1/8"   |             |             |                                 |                                 |
| 12'-0"                                  | 12'-4 3/4"  | 12'-2 7/16"                     | 8'-3 7/16"                      | 4'-5 1/8"   | 10'-3 7/16"   | 5'-5 1/8"   |             |             |                                 |                                 |
| > 12'-0"                                |             |                                 | Contact local Andersen supplier |             |               |             |             |             |                                 |                                 |

| Chart 9.1  |             | Two-Directional - Four Panel    |               |             |                                 |             |             |             |                                 |                                 |  |
|--|-------------|---------------------------------|---------------|-------------|---------------------------------|-------------|-------------|-------------|---------------------------------|---------------------------------|--|
| Head Jamb Depth at Astragal = 8 1/16", O.A. Frame Depth = 11 3/4", Pocket Depth = 1'-1 9/16" |             |                                 |               |             |                                 |             |             |             |                                 |                                 |  |
| Panel Height   | R.O. Height | Top of F.F. to Bottom of Header | Minimum Width |             | Maximum Width                   |             |             |             |                                 |                                 |  |
|  |             |                                 | R.O.          | Pocket R.O. | R.O.                            | Pocket R.O. | R.O.        | Pocket R.O. | R.O.                            | Pocket R.O.                     |  |
|  |             |                                 | Rated         |             |                                 |             | Not Rated   |             |                                 |                                 |  |
|  |             |                                 |               |             | Without Intermediate Stile      |             |             |             |                                 | With Intermediate Stile         |  |
| Contact local Andersen supplier  |             |                                 |               |             |                                 |             |             |             |                                 |                                 |  |
| < 6'-6"  |             |                                 |               |             |                                 |             |             |             |                                 |                                 |  |
| 6'-6"  | 6'-10 3/4"  | 6'-8 7/16"                      | 8'-4 7/16"    | 2'-7 1/8"   | 27'-8 7/16"                     | 7'-5 1/8"   | 47'-6 7/16" | 12'-5 1/8"  | Contact local Andersen supplier | Contact local Andersen supplier |  |
| 7'-0"  | 7'-4 3/4"   | 7'-2 7/16"                      | 9'-0 7/16"    | 2'-9 1/8"   |                                 |             |             |             |                                 |                                 |  |
| 7'-6"  | 7'-10 3/4"  | 7'-8 7/16"                      | 9'-8 7/16"    | 2'-11 1/8"  |                                 |             |             |             |                                 |                                 |  |
| 8'-0"  | 8'-4 3/4"   | 8'-2 7/16"                      | 10'-4 7/16"   | 3'-1 1/8"   |                                 |             |             |             |                                 |                                 |  |
| 8'-6"  | 8'-10 3/4"  | 8'-8 7/16"                      | 11'-0 7/16"   | 3'-3 3/8"   |                                 |             |             |             |                                 |                                 |  |
| 9'-0"  | 9'-4 3/4"   | 9'-2 7/16"                      | 11'-8 7/16"   | 3'-5 3/8"   | 25'-8 7/16"                     | 6'-11 1/8"  | 27'-8 7/16" | 7'-5 1/8"   |                                 |                                 |  |
| 9'-6"  | 9'-10 3/4"  | 9'-8 7/16"                      | 12'-4 7/16"   | 3'-7 3/8"   | 24'-4 7/16"                     | 6'-7 3/8"   |             |             |                                 |                                 |  |
| 10'-0"   | 10'-4 3/4"  | 10'-2 7/16"                     | 13'-0 7/16"   | 3'-9 3/8"   | 23'-8 7/16"                     | 6'-5 1/8"   |             |             |                                 |                                 |  |
| 10'-6"   | 10'-10 3/4" | 10'-8 7/16"                     | 13'-8 7/16"   | 3'-11 1/8"  | 22'-4 7/16"                     | 6'-1 1/8"   |             |             |                                 |                                 |  |
| 11'-0"   | 11'-4 3/4"  | 11'-2 7/16"                     | 14'-4 7/16"   | 4'-1 1/8"   | 21'-4 7/16"                     | 5'-10 1/8"  |             |             |                                 |                                 |  |
| 11'-6"   | 11'-10 3/4" | 11'-8 7/16"                     | 15'-0 7/16"   | 4'-3 3/8"   | 20'-4 7/16"                     | 5'-7 1/8"   |             |             |                                 |                                 |  |
| 12'-0"   | 12'-4 3/4"  | 12'-2 7/16"                     | 15'-8 7/16"   | 4'-5 1/8"   | 19'-6 7/16"                     | 5'-5 1/8"   |             |             |                                 |                                 |  |
| > 12'-0"   |             |                                 |               |             | Contact local Andersen supplier |             |             |             |                                 |                                 |  |

| Chart 9.2  |                                 | Two-Directional - Six Panel     |                            |             |               |            |             |            |                                 |                                 |                         |             |  |  |  |
|--|---------------------------------|---------------------------------|----------------------------|-------------|---------------|------------|-------------|------------|---------------------------------|---------------------------------|-------------------------|-------------|--|--|--|
| Head Jamb Depth at Astragal = 9 7⁄8", O.A. Frame Depth = 1'-5 5⁄16", Pocket Depth = 1'-7 1⁄16" |                                 |                                 |                            |             |               |            |             |            |                                 |                                 |                         |             |  |  |  |
| Panel Height   | R.O. Height                     | Top of F.F. to Bottom of Header | Minimum Width              |             | Maximum Width |            |             |            |                                 |                                 |                         |             |  |  |  |
|  |                                 |                                 | R.O.                       | Pocket R.O. | R.O.          |            | Pocket R.O. |            | R.O.                            | Pocket R.O.                     | R.O.                    | Pocket R.O. |  |  |  |
|  |                                 |                                 | Rated                      |             |               |            | Not Rated   |            |                                 |                                 |                         |             |  |  |  |
|  |                                 |                                 | Without Intermediate Stile |             |               |            |             |            |                                 |                                 | With Intermediate Stile |             |  |  |  |
| Contact local Andersen supplier  |                                 |                                 |                            |             |               |            |             |            |                                 |                                 |                         |             |  |  |  |
| 6'-6"  | 6'-10 3⁄4"                      | 6'-8 7⁄16"                      | 12'-1 7⁄16"                | 2'-7 1⁄8"   | 41'-1 7⁄16"   | 7'-5 1⁄8"  | 71'-1 7⁄16" | 12'-5 1⁄8" | Contact local Andersen supplier | Contact local Andersen supplier |                         |             |  |  |  |
| 7'-0"  | 7'-4 3⁄4"                       | 7'-2 7⁄16"                      | 13'-1 7⁄16"                | 2'-9 1⁄8"   |               |            | 41'-1 7⁄16" | 7'-5 1⁄8"  |                                 |                                 |                         |             |  |  |  |
| 7'-6"  | 7'-10 3⁄4"                      | 7'-8 7⁄16"                      | 14'-1 7⁄16"                | 2'-11 1⁄8"  |               |            |             |            |                                 |                                 |                         |             |  |  |  |
| 8'-0"  | 8'-4 3⁄4"                       | 8'-2 7⁄16"                      | 15'-1 7⁄16"                | 3'-1 1⁄8"   |               |            |             |            |                                 |                                 |                         |             |  |  |  |
| 8'-6"  | 8'-10 3⁄4"                      | 8'-8 7⁄16"                      | 16'-1 7⁄16"                | 3'-3 3⁄8"   |               |            |             |            |                                 |                                 |                         |             |  |  |  |
| 9'-0"  | 9'-4 3⁄4"                       | 9'-2 7⁄16"                      | 17'-1 7⁄16"                | 3'-5 1⁄8"   | 38'-1 7⁄16"   | 6'-11 1⁄8" |             |            |                                 |                                 |                         |             |  |  |  |
| 9'-6"  | 9'-10 3⁄4"                      | 9'-8 7⁄16"                      | 18'-1 7⁄16"                | 3'-7 1⁄8"   | 36'-1 7⁄16"   | 6'-7 1⁄8"  |             |            |                                 |                                 |                         |             |  |  |  |
| 10'-0"   | 10'-4 3⁄4"                      | 10'-2 7⁄16"                     | 19'-1 7⁄16"                | 3'-9 1⁄8"   | 35'-1 7⁄16"   | 6'-5 1⁄8"  |             |            |                                 |                                 |                         |             |  |  |  |
| 10'-6"   | 10'-10 3⁄4"                     | 10'-8 7⁄16"                     | 20'-1 7⁄16"                | 3'-11 1⁄8"  | 33'-1 7⁄16"   | 6'-1 1⁄8"  |             |            |                                 |                                 |                         |             |  |  |  |
| 11'-0"   | 11'-4 3⁄4"                      | 11'-2 7⁄16"                     | 21'-1 7⁄16"                | 4'-1 1⁄8"   | 31'-7 7⁄16"   | 5'-10 1⁄8" |             |            |                                 |                                 |                         |             |  |  |  |
| 11'-6"   | 11'-10 3⁄4"                     | 11'-8 7⁄16"                     | 22'-1 7⁄16"                | 4'-3 3⁄8"   | 30'-1 7⁄16"   | 5'-7 1⁄8"  |             |            |                                 |                                 |                         |             |  |  |  |
| 12'-0"   | 12'-4 3⁄4"                      | 12'-2 7⁄16"                     | 23'-1 7⁄16"                | 4'-5 1⁄8"   | 29'-1 7⁄16"   | 5'-5 1⁄8"  |             |            |                                 |                                 |                         |             |  |  |  |
| > 12'-0"   | Contact local Andersen supplier |                                 |                            |             |               |            |             |            |                                 |                                 |                         |             |  |  |  |




## Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications.  
Dimensions in parentheses are in millimeters.

See Page 22 for Glazing Accessories

Date: 7/11/18  
Scale: None

| Chart 10.0   |                                      |                                      | Two-Directional - Eight Panel         |                                     |                                       |                                    |                                      |                                     |                                 |                                 |                                       |                                     |  |  |
|--|--------------------------------------|--------------------------------------|---------------------------------------|-------------------------------------|---------------------------------------|------------------------------------|--------------------------------------|-------------------------------------|---------------------------------|---------------------------------|---------------------------------------|-------------------------------------|--|--|
| Head Jamb Depth at Astragal = 11 <sup>11</sup> / <sub>16</sub> " , O.A. Frame Depth = 1'-10 <sup>13</sup> / <sub>16</sub> " , Pocket Depth = 2'-0 <sup>9</sup> / <sub>16</sub> " |                                      |                                      |                                       |                                     |                                       |                                    |                                      |                                     |                                 |                                 |                                       |                                     |  |  |
| Panel Height   | R.O. Height                          | Top of F.F. to Bottom of Header      | Minimum Width                         |                                     | Maximum Width                         |                                    |                                      |                                     |                                 |                                 |                                       |                                     |  |  |
|  |                                      |                                      | R.O.                                  | Pocket R.O.                         | R.O.                                  |                                    | Pocket R.O.                          |                                     | R.O.                            |                                 | Pocket R.O.                           |                                     |  |  |
|  |                                      |                                      | Rated                                 |                                     |                                       |                                    |                                      |                                     |                                 |                                 | Not Rated                             |                                     |  |  |
|  |                                      |                                      | Without Intermediate Stile            |                                     |                                       |                                    |                                      |                                     | With Intermediate Stile         |                                 |                                       |                                     |  |  |
| Contact local Andersen supplier  |                                      |                                      |                                       |                                     |                                       |                                    |                                      |                                     |                                 |                                 |                                       |                                     |  |  |
| < 6'-6"  |                                      |                                      |                                       |                                     |                                       |                                    |                                      |                                     |                                 |                                 |                                       |                                     |  |  |
| 6'-6"  | 6'-10 <sup>3</sup> / <sub>4</sub> "  | 6'-8 <sup>7</sup> / <sub>16</sub> "  | 15'-10 <sup>7</sup> / <sub>16</sub> " | 2'-7 <sup>1</sup> / <sub>8</sub> "  | 43'-9 <sup>3</sup> / <sub>4</sub> "   | 6'-1"                              | 94'-6 <sup>7</sup> / <sub>16</sub> " | 12'-5 <sup>1</sup> / <sub>8</sub> " | Contact local Andersen supplier | Contact local Andersen supplier |                                       |                                     |  |  |
| 7'-0"  | 7'-4 <sup>3</sup> / <sub>4</sub> "   | 7'-2 <sup>7</sup> / <sub>16</sub> "  | 17'-2 <sup>7</sup> / <sub>16</sub> "  | 2'-9 <sup>1</sup> / <sub>8</sub> "  |                                       |                                    | 54'-6 <sup>7</sup> / <sub>16</sub> " | 7'-5 <sup>1</sup> / <sub>8</sub> "  |                                 |                                 |                                       |                                     |  |  |
| 7'-6"  | 7'-10 <sup>3</sup> / <sub>4</sub> "  | 7'-8 <sup>7</sup> / <sub>16</sub> "  | 18'-6 <sup>7</sup> / <sub>16</sub> "  | 2'-11 <sup>1</sup> / <sub>8</sub> " |                                       |                                    |                                      |                                     |                                 |                                 |                                       |                                     |  |  |
| 8'-0"  | 8'-4 <sup>3</sup> / <sub>4</sub> "   | 8'-2 <sup>7</sup> / <sub>16</sub> "  | 19'-10 <sup>7</sup> / <sub>16</sub> " | 3'-1 <sup>1</sup> / <sub>8</sub> "  |                                       |                                    |                                      |                                     |                                 |                                 |                                       |                                     |  |  |
| 8'-6"  | 8'-10 <sup>3</sup> / <sub>4</sub> "  | 8'-8 <sup>7</sup> / <sub>16</sub> "  | 21'-2 <sup>7</sup> / <sub>16</sub> "  | 3'-3 <sup>1</sup> / <sub>8</sub> "  |                                       |                                    |                                      |                                     |                                 |                                 |                                       |                                     |  |  |
| 9'-0"  | 9'-4 <sup>3</sup> / <sub>4</sub> "   | 9'-2 <sup>7</sup> / <sub>16</sub> "  | 22'-6 <sup>7</sup> / <sub>16</sub> "  | 3'-5 <sup>1</sup> / <sub>8</sub> "  |                                       |                                    |                                      |                                     |                                 |                                 |                                       |                                     |  |  |
| 9'-6"  | 9'-10 <sup>3</sup> / <sub>4</sub> "  | 9'-8 <sup>7</sup> / <sub>16</sub> "  | 23'-10 <sup>7</sup> / <sub>16</sub> " | 3'-7 <sup>1</sup> / <sub>8</sub> "  |                                       |                                    |                                      |                                     |                                 |                                 |                                       |                                     |  |  |
| 10'-0"   | 10'-4 <sup>3</sup> / <sub>4</sub> "  | 10'-2 <sup>7</sup> / <sub>16</sub> " | 25'-2 <sup>7</sup> / <sub>16</sub> "  | 3'-9 <sup>1</sup> / <sub>8</sub> "  |                                       |                                    |                                      |                                     |                                 |                                 |                                       |                                     |  |  |
| 10'-6"   | 10'-10 <sup>3</sup> / <sub>4</sub> " | 10'-8 <sup>7</sup> / <sub>16</sub> " | 26'-6 <sup>7</sup> / <sub>16</sub> "  | 3'-11 <sup>1</sup> / <sub>8</sub> " |                                       |                                    |                                      |                                     |                                 |                                 |                                       |                                     |  |  |
| 11'-0"   | 11'-4 <sup>3</sup> / <sub>4</sub> "  | 11'-2 <sup>7</sup> / <sub>16</sub> " | 27'-10 <sup>7</sup> / <sub>16</sub> " | 4'-1 <sup>1</sup> / <sub>8</sub> "  |                                       |                                    |                                      |                                     |                                 |                                 | 41'-10 <sup>7</sup> / <sub>16</sub> " | 5'-10 <sup>1</sup> / <sub>8</sub> " |  |  |
| 11'-6"   | 11'-10 <sup>3</sup> / <sub>4</sub> " | 11'-8 <sup>7</sup> / <sub>16</sub> " | 29'-2 <sup>7</sup> / <sub>16</sub> "  | 4'-3 <sup>1</sup> / <sub>8</sub> "  | 39'-10 <sup>7</sup> / <sub>16</sub> " | 5'-7 <sup>1</sup> / <sub>8</sub> " |                                      |                                     |                                 |                                 |                                       |                                     |  |  |
| 12'-0"   | 12'-4 <sup>3</sup> / <sub>4</sub> "  | 12'-2 <sup>7</sup> / <sub>16</sub> " | 30'-6 <sup>7</sup> / <sub>16</sub> "  | 4'-5 <sup>1</sup> / <sub>8</sub> "  | 38'-6 <sup>7</sup> / <sub>16</sub> "  | 5'-5 <sup>1</sup> / <sub>8</sub> " |                                      |                                     |                                 |                                 |                                       |                                     |  |  |
| > 12'-0"   |                                      |                                      | Contact local Andersen supplier       |                                     |                                       |                                    |                                      |                                     |                                 |                                 |                                       |                                     |  |  |



| Chart 10.1   |                                 | Two-Directional - Ten Panel     |                            |             |               |             |               |             |                                 |                                 |  |
|--|---------------------------------|---------------------------------|----------------------------|-------------|---------------|-------------|---------------|-------------|---------------------------------|---------------------------------|--|
| Head Jamb Depth at Astragal = 1'-1 9/16", O.A. Frame Depth = 2'-4 3/8", Pocket Depth = 2'-6 1/8" |                                 |                                 |                            |             |               |             |               |             |                                 |                                 |  |
| Panel Height   | R.O. Height                     | Top of F.F. to Bottom of Header | Minimum Width              |             | Maximum Width |             |               |             |                                 |                                 |  |
|  |                                 |                                 | R.O.                       | Pocket R.O. | R.O.          | Pocket R.O. | R.O.          | Pocket R.O. | R.O.                            | Pocket R.O.                     |  |
|  |                                 |                                 | Rated                      |             |               | Not Rated   |               |             |                                 |                                 |  |
|  |                                 |                                 | Without Intermediate Stile |             |               |             |               |             | With Intermediate Stile         |                                 |  |
| Contact local Andersen supplier  |                                 |                                 |                            |             |               |             |               |             |                                 |                                 |  |
| < 6'-6"  |                                 |                                 |                            |             |               |             |               |             |                                 |                                 |  |
| 6'-6"  | 6'-10 3/4"                      | 6'-8 7/16"                      | 19'-7 7/16"                | 2'-7 1/8"   | 43'-9 3/4"    | 5'-0 1/8"   | 117'-11 7/16" | 12'-5 1/8"  | Contact local Andersen supplier | Contact local Andersen supplier |  |
| 7'-0"  | 7'-4 3/4"                       | 7'-2 7/16"                      | 21'-3 7/16"                | 2'-9 1/8"   |               |             | 67'-11 7/16"  | 7'-5 1/8"   |                                 |                                 |  |
| 7'-6"  | 7'-10 3/4"                      | 7'-8 7/16"                      | 22'-11 7/16"               | 2'-11 1/8"  |               |             |               |             |                                 |                                 |  |
| 8'-0"  | 8'-4 3/4"                       | 8'-2 7/16"                      | 24'-7 7/16"                | 3'-1 1/8"   |               |             |               |             |                                 |                                 |  |
| 8'-6"  | 8'-10 3/4"                      | 8'-8 7/16"                      | 26'-3 7/16"                | 3'-3 1/8"   |               |             |               |             |                                 |                                 |  |
| 9'-0"  | 9'-4 3/4"                       | 9'-2 7/16"                      | 27'-11 7/16"               | 3'-5 1/8"   |               |             |               |             |                                 |                                 |  |
| 9'-6"  | 9'-10 3/4"                      | 9'-8 7/16"                      | 29'-7 7/16"                | 3'-7 1/8"   |               |             |               |             |                                 |                                 |  |
| 10'-0"   | 10'-4 3/4"                      | 10'-2 7/16"                     | 31'-3 7/16"                | 3'-9 1/8"   |               |             |               |             |                                 |                                 |  |
| 10'-6"   | 10'-10 3/4"                     | 10'-8 7/16"                     | 32'-11 7/16"               | 3'-11 1/8"  |               |             |               |             |                                 |                                 |  |
| 11'-0"   | 11'-4 3/4"                      | 11'-2 7/16"                     | 34'-7 7/16"                | 4'-1 1/8"   |               |             |               |             |                                 |                                 |  |
| 11'-6"   | 11'-10 3/4"                     | 11'-8 7/16"                     | 36'-3 7/16"                | 4'-3 1/8"   |               |             |               |             |                                 |                                 |  |
| 12'-0"   | 12'-4 3/4"                      | 12'-2 7/16"                     | 37'-11 7/16"               | 4'-5 1/8"   |               |             |               |             |                                 |                                 |  |
| > 12'-0"   | Contact local Andersen supplier |                                 |                            |             |               |             |               |             |                                 |                                 |  |

| Chart 10.2   |                                 | Two-Directional - Twelve Panel  |                            |             |               |             |              |             |                                 |                                 |  |
|--|---------------------------------|---------------------------------|----------------------------|-------------|---------------|-------------|--------------|-------------|---------------------------------|---------------------------------|--|
| Head Jamb Depth at Astragal = 1'-3 3⁄8", O.A. Frame Depth = 2'-9 7⁄8", Pocket Depth = 2'-11 5⁄8" |                                 |                                 |                            |             |               |             |              |             |                                 |                                 |  |
| Panel Height   | R.O. Height                     | Top of F.F. to Bottom of Header | Minimum Width              |             | Maximum Width |             |              |             |                                 |                                 |  |
|  |                                 |                                 | R.O.                       | Pocket R.O. | R.O.          | Pocket R.O. | R.O.         | Pocket R.O. | R.O.                            | Pocket R.O.                     |  |
|  |                                 |                                 | Rated                      |             |               | Not Rated   |              |             |                                 |                                 |  |
|  |                                 |                                 | Without Intermediate Stile |             |               |             |              |             | With Intermediate Stile         |                                 |  |
| < 6'-6"  | Contact local Andersen supplier |                                 |                            |             |               |             |              |             |                                 |                                 |  |
| 6'-6"  | 6'-10 3⁄4"                      | 6'-8 7⁄16"                      | 23'-4 7⁄16"                | 2'-7 1⁄8"   | 43'-9 3⁄4"    | 4'-3 9⁄16"  | 141'-4 7⁄16" | 12'-5 1⁄8"  | Contact local Andersen supplier | Contact local Andersen supplier |  |
| 7'-0"  | 7'-4 3⁄4"                       | 7'-2 7⁄16"                      | 25'-4 7⁄16"                | 2'-9 1⁄8"   |               |             |              |             |                                 |                                 |  |
| 7'-6"  | 7'-10 3⁄4"                      | 7'-8 7⁄16"                      | 27'-4 7⁄16"                | 2'-11 1⁄8"  |               |             |              |             |                                 |                                 |  |
| 8'-0"  | 8'-4 3⁄4"                       | 8'-2 7⁄16"                      | 29'-4 7⁄16"                | 3'-1 1⁄8"   |               |             |              |             |                                 |                                 |  |
| 8'-6"  | 8'-10 3⁄4"                      | 8'-8 7⁄16"                      | 31'-4 7⁄16"                | 3'-3 1⁄8"   |               |             |              |             |                                 |                                 |  |
| 9'-0"  | 9'-4 3⁄4"                       | 9'-2 7⁄16"                      | 33'-4 7⁄16"                | 3'-5 1⁄8"   |               |             |              |             |                                 |                                 |  |
| 9'-6"  | 9'-10 3⁄4"                      | 9'-8 7⁄16"                      | 35'-4 7⁄16"                | 3'-7 1⁄8"   |               |             |              |             |                                 |                                 |  |
| 10'-0"   | 10'-4 3⁄4"                      | 10'-2 7⁄16"                     | 37'-4 7⁄16"                | 3'-9 1⁄8"   |               |             |              |             |                                 |                                 |  |
| 10'-6"   | 10'-10 3⁄4"                     | 10'-8 7⁄16"                     | 39'-4 7⁄16"                | 3'-11 1⁄8"  |               |             |              |             |                                 |                                 |  |
| 11'-0"   | 11'-4 3⁄4"                      | 11'-2 7⁄16"                     | 41'-4 7⁄16"                | 4'-1 1⁄8"   |               |             |              |             |                                 |                                 |  |
| 11'-6"   | 11'-10 3⁄4"                     | 11'-8 7⁄16"                     | 43'-4 7⁄16"                | 4'-3 1⁄8"   |               |             |              |             |                                 |                                 |  |
| 12'-0"   | 12'-4 3⁄4"                      | 12'-2 7⁄16"                     | 45'-4 7⁄16"                | 4'-5 1⁄8"   |               |             |              |             |                                 |                                 |  |
| > 12'-0"   | Contact local Andersen supplier |                                 |                            |             |               |             |              |             |                                 |                                 |  |

## Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications.  
Dimensions in parentheses are in millimeters.


See Page 22 for Glazing Accessories

Date: 7/11/18  
Scale: None


# Big Doors

Weiland™ Pocket Liftslide  
Aluminum Wood - With Screens

**Andersen**®  
ARCHITECTURAL  
COLLECTION




**IMPORTANT**  
For more detailed  
information pertaining to  
product application. See the  
**Weiland® Liftslide  
Site Prep Guide.**




**A** Head  
**11** 2 Track System


**D** Head  
**11** 4 Track System




**B** Full Drainage Flush Sill  
**11** 2 Track System



**E** Full Drainage Flush Sill  
**11** 4 Track System



**C** Flush Sill  
**11** 2 Track System



**F** Flush Sill  
**11** 4 Track System

## Notes:




Details have been optimized for use in architectural software and do not match manufacturing specifications.  
Dimensions in parentheses are in millimeters.

See Page 22 for Glazing Accessories

Date: 7/11/18  
Scale: 1 1/2" (38) = 1' (305)

## IMPORTANT

For more detailed information pertaining to product application. See the **Weiland® Liftslide Site Prep Guide.**



## Notes:


Details have been optimized for use in architectural software and do not match manufacturing specifications.  
Dimensions in parentheses are in millimeters.

See Page 22 for Glazing Accessories



Date: 7/11/18  
Scale: 1 1/2" (38) = 1' (305)

# Big Doors

## Weiland™ Pocket Liftslide Aluminum Wood - With Screens



**IMPORTANT**  
For more detailed information pertaining to product application. See the Weiland® Liftslide Site Prep Guide.



### Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications. Dimensions in parentheses are in millimeters.

See Page 22 for Glazing Accessories

Date: 7/11/18  
Scale: 1 1/2" (38) = 1' (305)


# Big Doors

Weiland™ Pocket Liftslide  
Aluminum Wood - With Screens

**Andersen®**  
ARCHITECTURAL  
COLLECTION

## IMPORTANT

For more detailed information pertaining to product application. See the Weiland® Liftslide Site Prep Guide.



## Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications. Dimensions in parentheses are in millimeters.

See Page 22 for Glazing Accessories


Date: 7/11/18  
Scale: 1 1/2" (38) = 1' (305)

# Big Doors

Weiland™ Pocket Liftslide  
Aluminum Wood - With Screens

## IMPORTANT

For more detailed information pertaining to product application. See the **Weiland® Liftslide Site Prep Guide.**



## Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications. Dimensions in parentheses are in millimeters.

See Page 22 for Glazing Accessories

Date: 7/11/18  
Scale: 1 1/2" (38) = 1' (305)



# Big Doors

Weiland™ Pocket Liftslide  
Aluminum Wood - With Screens



## IMPORTANT

For more detailed information pertaining to product application. See the **Weiland® Liftslide Site Prep Guide.**



## Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications. Dimensions in parentheses are in millimeters.

See Page 22 for Glazing Accessories

Date: 7/11/18  
Scale: 1 1/2" (38) = 1' (305)




# Big Doors

Weiland™ Pocket Liftslide  
Aluminum Wood - With Screens



## IMPORTANT

For more detailed information pertaining to product application. See the Weiland® Liftslide Site Prep Guide.



## Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications. Dimensions in parentheses are in millimeters.

See Page 22 for Glazing Accessories

Date: 7/11/18  
Scale: 1 1/2" (38) = 1' (305)


# Big Doors

Weiland™ Pocket Liftslide  
Aluminum Wood - With Screens



## IMPORTANT

For more detailed information pertaining to product application. See the Weiland® Liftslide Site Prep Guide.



## Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications. Dimensions in parentheses are in millimeters.

See Page 22 for Glazing Accessories

Date: 7/11/18  
Scale:  $1\frac{1}{2}"$  (38) = 1' (305)


# Big Doors

Weiland™ Pocket Liftslide  
Aluminum Wood - With Screens



## IMPORTANT

For more detailed information pertaining to product application. See the Weiland® Liftslide Site Prep Guide.



## Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications. Dimensions in parentheses are in millimeters.

See Page 22 for Glazing Accessories

Date: 7/11/18  
Scale: 1 1/2" (38) = 1' (305)


# Big Doors

Weiland™ Pocket Liftslide  
Aluminum Wood - With Screens



## IMPORTANT

For more detailed information pertaining to product application. See the Weiland® Liftslide Site Prep Guide.



## Notes:


Details have been optimized for use in architectural software and do not match manufacturing specifications. Dimensions in parentheses are in millimeters.

See Page 22 for Glazing Accessories


Date: 7/11/18  
Scale: 1 1/2" (38) = 1' (305)

# Big Doors


Weiland™ Pocket Liftslide  
Aluminum Wood - With Screens



**A** Astragal  
21



**C** Screen Interlock  
21



**B** Panel Interlock  
21

## Notes:




Details have been optimized for use in architectural software and do not match manufacturing specifications.  
Dimensions in parentheses are in millimeters.

See Page 22 for Glazing Accessories




Date: 7/11/18  
Scale: 3" (76) = 1' (305)

# Big Doors





Weiland™ Pocket Liftslide  
Aluminum Wood - With Screens



**J**  
22 Intermediate Rail



**K**  
22 Intermediate Stile



## Notes:

Details have been optimized for use in architectural software and do not match manufacturing specifications.  
Dimensions in parentheses are in millimeters.

Date: 7/11/18  
Scale: 6" (152) = 1' (305)