

SUMMARY TEST REPORT

FOR: Andersen Corporation Report Number: 10741.03-201-47 100 Fourth Avenue North Bayport, MN 55003 Report Date: 04/02/2018

Test Record Retention End Date: 03/20/2022

Rating

SERIES TESTED: CASEMENT WINDOW

MODEL TESTED: 100 SERIES CASEMENT WINDOW / 100CD3024-2 IG

NAFS-17/-11/-08 Class LC-PG50 Size Tested 71.5 x 27.4 in. DP +50/-50 psf*

Test Results Summary

Operating Force36 N (8 lbf)Resistance to Air Infiltration0.09 cfm/ft² (ASTM E283)Resistance to Water PenetrationPass at DP50 (ASTM E547)Resistance to Structural LoadingPass at DP +50/-50 (ASTM E330)Forced Entry ResistancePass (ASTM F 588)

CAN/CSA A440-00, Evaluation to the prescriptive requirements were not performed

<u>Test</u>	Kating
Operating Ease	36 N (8 lbf)
Air Tightness	A3
Water Tightness	В3
Wind Load Resistance	C3
Blow-Out	C3
Forced Entry Resistance	F10
Screen Push-out	S1

	See ATI Report No. 10741.01-201-47 and 10741.02-201-47 for complete test results.
REFERENCE:	* Reference Intertek-ATI Report No. I0739.01-201-47, dated 02/15/18 for
	complete Gateway test specimen description and test results.

A copy of this report will be retained by Intertek-ATI for a period of four years. This report is the exclusive property of the client named herein and is applicable to the sample tested. Results obtained are tested values and do not constitute an opinion or endorsement by this laboratory.

INTERTEK-ATI INTERTEK-ATI

Tony D. Gavin Daniel A. Johnson

Technician Director of Regional Operations

