



Telephone: 651-636-3835 Facsimile: 717-764-4129 www.intertek.com/building

SUMMARY TEST REPORT

FOR: Andersen Corporation Report Number: 10745.03-201-47 100 Fourth Avenue North Bayport, MN 55003 Report Date: 04/02/2018

Test Record Retention End Date: 03/19/2022

See ATI Report No. 10745.01-201-47 and 10745.02-201-47 for complete test results.

SERIES TESTED: CASEMENT WINDOW

MODEL TESTED: 100 SERIES CASEMENT WINDOW / 100CFP30-6056-30 IG

NAFS-17/-11/-08 Class LC-PG50 Size Tested 143.5 x 65.5 in. DP +50/-50 psf

Test Results Summary

Operating Force36 N (8 lbf)Resistance to Air Infiltration0.13 cfm/ft² (ASTM E283)Resistance to Water PenetrationPass at DP50 (ASTM E547)Resistance to Structural LoadingPass at DP +50/-50 (ASTM E330)Forced Entry ResistancePass (ASTM F 588)

CAN/CSA A440-00, Evaluation to the prescriptive requirements were not performed

| <u>Test</u> | Rating |
|-------------------------|--------------|
| Operating Ease | 36 N (8 lbf) |
| Air Tightness | A2 |
| Water Tightness | В3 |
| Wind Load Resistance | C3 |
| Blow-Out | C3 |
| Forced Entry Resistance | F10 |
| Screen Push-out | S1 |

A copy of this report will be retained by Intertek-ATI for a period of four years. This report is the exclusive property of the client named herein and is applicable to the sample tested. Results obtained are tested values and do not constitute an opinion or endorsement by this laboratory.

INTERTEK-ATI INTERTEK-ATI

Tony D. Gavin Daniel A. Johnson

Technician Director of Regional Operations

