



Telephone: 651-636-3835 Facsimile: 717-764-4129 www.intertek.com/building

## **SUMMARY TEST REPORT**

FOR: Andersen Corporation Report Number: N7097.02-201-47

100 Fourth Avenue North

Bayport, MN 55003

Report Date: 05/04/22

Test Record Retention End Date: 04/20/26

Series Model:

A-Series Casement Window - Stationary with PG Upgrade/ACW3080S
PGUP IG

Specification/Standards:	Rating/Results
NAFS 17, 11	Class LC-PG70 Size Tested 35.3 x 95.3 in.
	DP +70/-70 psf
CSA A440S1-19, 17	Class LC-PG70 Size Tested 895 x 2419 mm
	DP+3360/-3360 Pa
	Resistance to Water Penetration Test Pressure: 510 Pa
	Canadian Air Infiltration/Exfiltration Level = Fixed
ASTM E1886/E1996	N/A
TAS 202	N/A
TAS 201/203	N/A

Test	Results Summary
Air Infiltration per ASTM E283:	<0.05 L/s/m <sup>2</sup> (<0.01 cfm/ft <sup>2</sup> )
Air Exfiltration per ASTM E283:	<0.05 L/s/m <sup>2</sup> (<0.01 cfm/ft <sup>2</sup> )
Operating Force to Initiate:	N/A
Operating Force to Maintain:	N/A
Operating Force of locks:	N/A
Forced Entry Resistance per ASTM F588:	Grade 10 - Type D
Reference:	See Intertek B&C Report No. N7097.01-201-47 for complete test results.

A copy of this report will be retained by Intertek B&C for a period of four years. This report is the exclusive property of the client named herein and is applicable to the sample tested. Results obtained are tested values and do not constitute on opinion or endorsement by this laboratory.

## For INTERTEK B&C:

**COMPLETED BY:** Karl Lips **REVIEWED BY:** Eric Schoenthaler Senior Technician -Lab Manager - Building & **Building & Construction** TITLE: Construction TITLE: **SIGNATURE: SIGNATURE:** DATE: 05/04/22 DATE: 05/04/22 KL: es/wma