



Telephone: 651-636-3835 Facsimile: 717-764-4129 www.intertek.com/building

SUMMARY TEST REPORT

FOR: Andersen Corporation Report Number: N2651.02-201-44-R1

100 Fourth Avenue NorthTest End Date:02/10/2022Bayport, MN 55003Revised Report Date:04/05/2022Test Record Retention End Date:02/10/2026

Series Model:

A-Series Contemporary Frenchwood Hinged Patio Door – Inswing
FWHICD64100AP

Specification/Standards:	Rating/Results	
NAFS 17, 11	Class LC-PG45 Size Tested 75.3" x 119.5"	
	DP+45/-55	
CSA A440S1-19, 17	Class LC-PG45 Size Tested 1911 mm x 3035 mm	
	DP+2160/-2640 Pa	
	Resistance to Water Penetration Test Pressure: 330 Pa	
	Canadian Air Infiltration/Exfiltration Level = A3	

Test	Results Summary	
Air Infiltration per ASTM E283:	0.1 L/s/m² (0.01 cfm/ft²)	
Air Exfiltration per ASTM E283:	0.3 L/s/m² (0.05 cfm/ft²)	
Force to latch:	40 N (9 lbf)	
Forced Entry Resistance per AAMA	Pass	
1304:		
Reference:	See Intertek B&C Report No. N2651.01-201-44-R1 for complete test results.	

A copy of this report will be retained by Intertek B&C for a period of four years. This report is the exclusive property of the client named herein and is applicable to the sample tested. Results obtained are tested values and do not constitute on opinion or endorsement by this laboratory.

For INTERTEK B&C:

COMPLETED BY:	Dan Wadzinski	REVIEWED BY:	Daniel A. Johnson
	Project Manager –		Director – Regional
TITLE:	Building & Construction	TITLE:	Operations
SIGNATURE:		SIGNATURE:	
DATE:	04/05/22	DATE:	04/05/22
DW: daj/wma			

REVISION # DATE PAGES REVISION

0 02/17/22 N/A Original Report Issue
Revised report. Report revised to correct

1 04/05/22 1 product name.