



Telephone: 651-636-3835 Facsimile: 717-764-4129 www.intertek.com/building

SUMMARY TEST REPORT

FOR: Andersen Corporation Report Number: N2664.02-201-44-R1

100 Fourth Avenue North

Bayport, MN 55003

Revised Report Date: 02/14/2022

Test Record Retention End Date: 02/14/2026

Series Model:

A-Series Contemporary Frenchwood Hinged Patio Door – Outswing
FWOCD33100S

Specification/Standards:	Rating/Results
NAFS 17, 11	Class LC-PG45 Size Tested 38.1" x 119.5"
	DP+45/-55
CSA A440S1-19, 17	Class LC-PG45 Size Tested 968 mm x 3035 mm
	DP+2160/-2640 Pa
	Resistance to Water Penetration Test Pressure: 330 Pa
	Canadian Air Infiltration/Exfiltration Level = A3

Test	Results Summary
Air Infiltration per ASTM E283:	0.1 L/s/m ² (0.02 cfm/ft ²)
Air Exfiltration per ASTM E283:	0.3 L/s/m ² (0.06 cfm/ft ²)
Force to latch:	N/A
Forced Entry Resistance per ASTM F588:	Type D: Pass
Reference:	See Intertek B&C Report No. N2664.01-201-44-R1 for complete test results.

A copy of this report will be retained by Intertek B&C for a period of four years. This report is the exclusive property of the client named herein and is applicable to the sample tested. Results obtained are tested values and do not constitute on opinion or endorsement by this laboratory.

For INTERTEK B&C:

Dan Wadzinski Daniel A. Johnson **COMPLETED BY: REVIEWED BY:** Project Manager -Director – Regional **Building & Construction** TITLE: TITLE: Operations **SIGNATURE: SIGNATURE:** 04/05/22 04/05/22 DATE: DATE: DW: daj/wma

REVISION #DATEPAGESREVISION003/24/22N/AOriginal Report IssueRevised report. Report revised to correct104/05/221product name.