



SUMMARY TEST REPORT

FOR: Andersen E-Series/Eagle Window & Door

2045 Kerper Boulevard Dubuque, Iowa 52001 Report Number: E6414.03-201-44

Test End Date: 04/07/2015 Report Date: 05/16/2015

Test Record Retention End Date: 04/07/2019

SERIES TESTED: 3080 Series 05 E-Series Hinged Patio Door Sidelight – Inswing - SL1 with

Harbor Master IG

MODEL TESTED: Aluminum Clad Wood Fixed Door with Impact Glazing (O)

NAFS-08/-11 Class LC-PG45 Size Tested 927 x 2438 mm (36.5. x 96 in.)-FD Class LC-PG45 Size Tested 927 x 2438 mm (36.5. x 96 in.)-SLT

<u>Test</u> <u>Results Summary</u>

Resistance to Air Infiltration
Resistance to Water Penetration
Resistance to Structural Loading

ASTM E1886 / ASTM E1996

Forced Entry Resistance

0.04 cfm/ft² (ASTM E283) Pass at DP45 (ASTM E547/ ASTM E331) Pass at DP +50/-65 (ASTM E330) Pass (ASTM F588)

Test Results Summary

Impact No rips, tears or penetrations, Missile D, Zone 4
Pressure Cycling DP +50/-65 psf

REFERENCE:

See ATI Report No. E6414.01-201-44, and E6414.02-201-44 for complete test results.

A copy of this report will be retained by Intertek-ATI for a period of four years. This report is the exclusive property of the client named herein and is applicable to the sample tested. Results obtained are tested values and do not constitute an opinion or endorsement by this laboratory.

INTERTEK-ATI: INTERTEK-ATI:

Eric J. Schoenthaler Daniel A. Johnson

Project Manager Director - Regional Operations