



Class LC-PG30 Size Tested 71.3 x 82.4 in. DP+30/-35

**Results Summary** 

## **SUMMARY TEST REPORT**

FOR: Andersen Corporation

NAFS-08/-11

Test

100 Fourth Avenue North Bayport, MN 55003 Report Number: D8513.03-201-47 Test End Date: 07/14/2014

Report Date: 09/02/2014
Test Record Retention End Date: 07/14/2018

SERIES TESTED: 200 Series Hinged Patio Door - Inswing/ISPD60611AP IG

MODEL TESTED Fiberglass Hinged Glass Door (XX)

Force to Latch
Resistance to Air Infiltration
Resistance to Water Penetration

40 N (9 lbf) max.
0.07 cfm/ft² (ASTM E283)
Pass at DP30 (ASTM E547)

Resistance to Structural Loading Pass at DP30 (ASTM E330)
Forced Entry Resistance Pass (AAMA 1304)

CAN/CGSB-82.1-M89, Evaluation to the prescriptive requirements were not performed

TestRatingForce to Latch40 N (9 lbf)Air TightnessA3Water TightnessB2Wind Load ResistanceC3Blow-OutC3Resistance to Forced EntryAAMA 1304

REFERENCE:	See ATI Report No. D8513.01-201-47 and D8513.02-201-47 for complete test
	results.

A copy of this report will be retained by ATI for a period of four years. This report is the exclusive property of the client named herein and is applicable to the sample tested. Results obtained are tested values and do not constitute an opinion or endorsement by this laboratory.

## ARCHITECTURAL TESTING, INC

ARCHITECTURAL TESTING, INC

Karl A. Lips-Eakins Daniel A. Johnson

Senior Technician Director - Regional Operations