

100 SERIES AWNING WINDOWS

Table of Awning Window Sizes

Scale 1/8" (3) = 1'-0" (305) – 1:96


Window Dimension	1'-5 1/2"	1'-11 1/2"	2'-5 1/2"	2'-11 1/2"	3'-5 1/2"	3'-11 1/2"
	(445)	(597)	(749)	(902)	(1054)	(1207)
Minimum Rough Opening	1'-6"	2'-0"	2'-6"	3'-0"	3'-6"	4'-0"
	(457)	(610)	(762)	(914)	(1067)	(1219)
Unobstructed Glass	11 1/4"	17 1/4"	23 1/4"	29 1/4"	35 1/4"	41 1/4"
	(286)	(438)	(591)	(743)	(895)	(1048)

CUSTOM WIDTHS – 17 1/2" to 47 1/2"					
CUSTOM HEIGHTS – 17 1/2" to 35 1/2"	1'-5 1/2"	1'-6"	1'-11 1/2"	2'-0"	2'-5 1/2"
	(445)	(457)	(597)	(610)	(749)
	11 1/4"	11 1/4"	17 1/4"	17 1/4"	23 1/4"
	(286)	(286)	(438)	(438)	(591)
	1616	2016	2616	3016	3616
	1620	2020	2620	3020	3620
	1626	2026	2626	3026	3626
	1630	2030	2630	3030	3630
	4016	4020	4026	4030	

- Window Dimension always refers to outside frame-to-frame dimension.
- Minimum Rough Opening dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.
- Dimensions in parentheses are in millimeters.



Custom-size windows are available in 1/8" (3) increments.



Venting Stationary

Choose venting or stationary. **Awning windows must be installed to vent as shown and should not be rotated and used as a hopper.**

100 SERIES AWNING WINDOWS




Custom Sizes and Specification Formulas



100 Series custom-size windows are available in 1/8" (3) increments between minimum and maximum widths and heights shown. Some restrictions apply.

Awning Windows



Single			
Clear Opening 	Width = window width - 5.694" (145) Depth = 8.000" (203)	Minimum R.O. 	1 3/8" & 1" Flange Setback Frames Width = window width + 1/2" (13) Height = window height + 1/2" (13)
			Insert & Flush Fin Frames Width = window width + 3/8" (10) Height = window height + 3/8" (10)
Vent Opening 	Width = window width - 5.694" (145) Depth = 8.000" (203)	Unobst. Glass 	Width = window width - 6.250" (159) Height = window height - 6.250" (159)

* Awning windows do not meet clear opening area of 5.7 sq.ft. or 0.53 m², clear opening width of 20" (508) and clear opening height of 24" (610).