

Table of Picture Window Sizes

Scale 1/8" (3) = 1'-0" (305) – 1:96

Window Dimension	2'-11 1/2" (902)	3'-11 1/2" (1207)	4'-5 1/2" (1359)	4'-8 1/2" (1435)	4'-11 1/2" (1511)	5'-5 1/2" (1664)	5'-11 1/2" (1816)
Minimum Rough Opening	3'-0" (914)	4'-0" (1219)	4'-6" (1372)	4'-9" (1448)	5'-0" (1524)	5'-6" (1676)	6'-0" (1829)
Unobstructed Glass	29 1/2" (749)	41 1/2" (1054)	47 1/2" (1207)	50 1/2" (1283)	53 1/2" (1359)	59 1/2" (1511)	65 1/2" (1664)

2'-11 1/2" (902)	3'-0" (914)	29 1/2" (749)							
3'-11 1/2" (1207)	4'-0" (1219)	41 1/2" (1054)	244FX3030	244FX4030	244FX4630	244FX4930	244FX5030	244FX5630	244FX6030
4'-5 1/2" (1359)	4'-6" (1372)	47 1/2" (1207)							
3'-11 1/2" (1207)	4'-0" (1219)	41 1/2" (1054)	244FX3040	244FX4040	244FX4640	244FX4940	244FX5040	244FX5640	244FX6040
4'-5 1/2" (1359)	4'-6" (1372)	47 1/2" (1207)							
4'-5 1/2" (1359)	4'-6" (1372)	47 1/2" (1207)	244FX3046	244FX4046	244FX4646	244FX4946	244FX5046	244FX5646	244FX6046
4'-11 1/2" (1511)	5'-0" (1524)	53 1/2" (1359)							
4'-11 1/2" (1511)	5'-0" (1524)	53 1/2" (1359)	244FX3050	244FX4050	244FX4650	244FX4950	244FX5050	244FX5650	244FX6050

Basic frame dimensions for gliding windows and picture windows are different. When joining, specify common extension jamb dimensions i.e. 4 9/16" (116), 6 9/16" (167).

- "Window Dimension" always refers to outside frame to frame dimension.
- **"Minimum Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.**
- Dimensions in parentheses are in millimeters.